



TIRE SPECIFICATIONS

VICTRA | RC-1



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
205/50ZR15	86W	BSW	22.9	8.6	5.5	6.5	7.5	6/32	1168	51
225/45ZR15	87W	BSW	22.8	9.1	7.0	7.5	8.5	6/32	1201	51
245/40ZR15	88W	BSW	22.5	9.8	8.0	8.5	9.5	6/32	1235	51
225/45ZR17	94W XL	BSW	24.8	9.1	7.0	7.5	8.5	6/32	1477	50
235/40ZR17	90W	BSW	24.3	9.6	8.0	8.5	9.5	6/32	1323	51
245/45ZR17	99W XL	BSW	25.5	9.8	7.5	8.0	9.0	6/32	1709	50
255/40ZR17	94W	BSW	24.8	10.5	8.5	9.0	10.0	6/32	1477	51
275/35ZR17	94W	BSW	24.6	10.9	9.0	9.5	11.0	6/32	1477	51
275/40ZR17	98W	BSW	25.6	10.9	9.0	9.5	11.0	6/32	1653	51
235/40ZR18	91W	BSW	25.5	9.7	8.0	8.5	9.5	6/32	1356	51
265/35ZR18	97W XL	BSW	25.5	10.9	9.0	9.5	10.5	6/32	1609	50
275/35ZR18	99W XL	BSW	25.4	11.2	9.0	9.5	11.0	6/32	1709	50

VICTRA | R19



TIRE SIZE	SERVICE DESCRIPTION	COMPOUND	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
LEFT											
185/70R13	86Q	HARD	BSW	23.2	7.4	4.5	5.5	6.0	13/32	1168	44
185/70R13	86Q	MEDIUM	BSW	23.2	7.4	4.5	5.5	6.0	13/32	1168	44
185/70R13	86Q	SOFT	BSW	23.2	7.4	4.5	5.5	6.0	13/32	1168	44
175/65R14	82Q	HARD	BSW	23.1	6.9	5.0	5.0	6.0	13/32	1047	44
175/65R14	82Q	MEDIUM	BSW	23.1	6.9	5.0	5.0	6.0	13/32	1047	44
175/65R14	82Q	SOFT	BSW	23.1	6.9	5.0	5.0	6.0	13/32	1047	44
185/65R14	86Q	HARD	BSW	23.5	7.3	5.0	5.5	6.5	13/32	1168	44
185/65R14	86Q	MEDIUM	BSW	23.5	7.3	5.0	5.5	6.5	13/32	1168	44
185/65R14	86Q	SOFT	BSW	23.5	7.3	5.0	5.5	6.5	13/32	1168	44
185/65R15	88Q	HARD	BSW	24.6	7.3	5.0	5.5	6.5	13/32	1235	44
185/65R15	88Q	MEDIUM	BSW	24.6	7.3	5.0	5.5	6.5	13/32	1235	44
185/65R15	88Q	SOFT	BSW	24.6	7.3	5.0	5.5	6.5	13/32	1235	44
195/65R15	91Q	HARD	BSW	25.1	7.7	5.5	6.0	7.0	13/32	1356	44
195/65R15	91Q	MEDIUM	BSW	25.1	7.7	5.5	6.0	7.0	13/32	1356	44
195/65R15	91Q	SOFT	BSW	25.1	7.7	5.5	6.0	7.0	13/32	1356	44
205/65R15	94Q	HARD	BSW	25.6	8.1	5.5	6.0	7.5	13/32	1477	44
205/65R15	94Q	MEDIUM	BSW	25.6	8.1	5.5	6.0	7.5	13/32	1477	44
205/65R15	94Q	SOFT	BSW	25.6	8.1	5.5	6.0	7.5	13/32	1477	44

VICTRA | R19 CONTINUED

TIRE SIZE	SERVICE DESCRIPTION	COMPOUND	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
RIGHT											
185/70R13	86Q	HARD	BSW	23.2	7.4	4.5	5.5	6.0	13/36	1168	44
185/70R13	86Q	MEDIUM	BSW	23.2	7.4	4.5	5.5	6.0	13/34	1168	44
185/70R13	86Q	SOFT	BSW	23.2	7.4	4.5	5.5	6.0	13/32	1168	44
175/65R14	82Q	HARD	BSW	23.1	6.9	5.0	5.0	6.0	13/32	1047	44
175/65R14	82Q	MEDIUM	BSW	23.1	6.9	5.0	5.0	6.0	13/32	1047	44
175/65R14	82Q	SOFT	BSW	23.1	6.9	5.0	5.0	6.0	13/32	1047	44
185/65R14	86Q	HARD	BSW	23.5	7.3	5.0	5.5	6.5	13/32	1168	44
185/65R14	86Q	MEDIUM	BSW	23.5	7.3	5.0	5.5	6.5	13/32	1168	44
185/65R14	86Q	SOFT	BSW	23.5	7.3	5.0	5.5	6.5	13/32	1168	44
185/65R15	88Q	HARD	BSW	24.6	7.3	5.0	5.5	6.5	13/32	1235	44
185/65R15	88Q	MEDIUM	BSW	24.6	7.3	5.0	5.5	6.5	13/32	1235	44
185/65R15	88Q	SOFT	BSW	24.6	7.3	5.0	5.5	6.5	13/32	1235	44
195/65R15	91Q	HARD	BSW	25.1	7.7	5.5	6.0	7.0	13/32	1356	44
195/65R15	91Q	MEDIUM	BSW	25.1	7.7	5.5	6.0	7.0	13/32	1356	44
195/65R15	91Q	SOFT	BSW	25.1	7.7	5.5	6.0	7.0	13/32	1356	44
205/65R15	94Q	HARD	BSW	25.6	8.1	5.5	6.0	7.5	13/32	1477	44
205/65R15	94Q	MEDIUM	BSW	25.6	8.1	5.5	6.0	7.5	13/32	1477	44
205/65R15	94Q	SOFT	BSW	25.6	8.1	5.5	6.0	7.5	13/32	1477	44



VICTRA | VR-1

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
205/50ZR15#	86W	BSW	23.1	8.4	5.5	6.5	7.5	9/32	1168	51
225/45ZR15#	87W	BSW	23.0	8.8	7.0	7.5	8.5	9/32	1202	51
245/40ZR15#	88W	BSW	22.7	9.8	8.0	8.5	9.5	9/32	1235	51
205/55R16#	91V	BSW	24.8	8.3	5.5	6.5	7.5	9/32	1356	51
215/40ZR16#	86W XL	BSW	22.8	8.6	7.0	7.5	8.5	9/32	1169	50
215/40ZR17#	83W	BSW	23.7	8.6	7.0	7.5	8.5	9/32	1074	51
225/45ZR17#	94W XL	BSW	25.2	8.9	7.0	7.5	8.5	9/32	1477	50
245/40ZR17#	95W XL	BSW	24.7	9.7	8.0	8.5	9.5	9/32	1521	50
255/40ZR17#	94W	BSW	25.0	10.2	8.5	9.0	10.0	9/32	1477	51
225/40ZR18#	88W	BSW	25.2	9.1	7.5	8.0	9.0	9/32	1235	51
245/40ZR18#	93W	BSW	25.7	9.7	8.0	8.5	9.5	9/32	1433	51
255/35ZR18#	94W XL	BSW	25.0	10.4	8.5	9.0	10.0	9/32	1477	50
265/35ZR18#	97W XL	BSW	25.5	10.8	9.0	9.5	10.5	9/32	1609	50
275/35ZR18#	99W XL	BSW	25.7	11.1	9.0	9.5	11.0	9/32	1709	50
285/35ZR18#	101W XL	BSW	25.9	11.6	9.5	10.0	11.0	9/32	1819	50
295/40ZR18#	103W	BSW	27.4	11.9	10.0	10.5	11.5	9/32	1929	51



- S2 Compound; XL - Extra Load; BSW - Black Sidewall

VICTRA | M36+



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
205/55ZRF16	91W	BSW	24.9	8.1	5.5	6.5	7.5	10/32	1356	51
225/50RF16	92V	BSW	24.9	8.9	6.0	7.0	8.0	10/32	1389	44
225/55ZRF16	95W	BSW	25.7	8.9	6.0	7.0	8.0	10/32	1521	51
205/50ZRF17	93W XL	BSW	25.1	8.1	5.5	6.5	7.5	10/32	1433	50
225/45ZRF17	91W	BSW	25.0	8.9	7.0	7.5	8.5	10/32	1356	51
225/50ZRF17	94W	BSW	25.9	8.9	6.0	7.0	8.0	10/32	1477	51
225/55ZRF17	97W	BSW	26.8	8.9	6.0	7.0	8.0	10/32	1609	51
245/45ZRF17	95W	BSW	25.7	9.6	7.5	8.0	9.0	10/32	1521	51
225/40ZRF18	92W	BSW	25.1	8.9	7.5	8.0	9.0	10/32	1389	50
225/45ZRF18	91W	BSW	25.9	9.6	7.0	7.5	8.5	10/32	1356	51
245/40ZRF18	93W	BSW	25.7	9.6	8.0	8.5	9.5	10/32	1433	51
245/45ZRF18	96W	BSW	26.7	9.6	7.5	8.0	9.0	10/32	1565	51
245/50ZRF18	100W	BSW	27.7	9.6	7.0	7.5	8.5	10/32	1763	51
255/40ZRF18	95W	BSW	26.0	10.0	8.5	9.0	10.0	10/32	1521	51
255/55ZRF18	109W	BSW	27.8	10.0	7.0	8.0	9.0	10/32	2271	50
245/40ZRF19	94W	BSW	26.7	9.6	8.0	8.5	9.5	10/32	1477	51
255/50ZRF19	107W	BSW	26.5	10.0	7.0	8.0	9.0	10/32	2149	50

VICTRA | SPORT 5



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
225/45ZR17	94Y XL	BSW	25.0	8.9	7.0	7.5	8.5	9/32	1477	50
235/45ZR17	97Y XL	BSW	25.4	9.3	7.5	8.0	9.0	9/32	1609	50
245/40ZR17	95Y XL	BSW	24.7	9.6	8.0	8.5	9.5	9/32	1521	50
245/45ZR17	99Y XL	BSW	25.7	9.6	7.5	8.0	9.0	9/32	1709	50
215/40ZR18	89Y XL	BSW	24.8	8.5	7.0	7.5	8.5	9/32	1279	50
225/40ZR18	92Y XL	BSW	25.1	8.9	7.5	8.0	9.0	9/32	1389	50
225/45ZR18	95Y XL	BSW	25.9	8.9	7.0	7.5	8.5	9/32	1521	50
235/40ZR18	95Y XL	BSW	25.4	9.3	8.0	8.5	9.5	9/32	1521	50
235/45ZR18	98Y XL	BSW	26.3	9.3	7.5	8.0	9.0	9/32	1653	50
245/35ZR18	92Y XL	BSW	24.8	9.6	8.0	8.5	9.5	9/32	1389	50
245/40ZR18	97Y XL	BSW	25.7	9.6	8.0	8.5	9.5	9/32	1609	50
245/45ZR18	100Y XL	BSW	27.1	9.6	7.5	8.0	9.0	9/32	1764	50
255/35ZR18	94Y XL	BSW	25.0	10.0	8.5	9.0	10.0	9/32	1477	50
265/35ZR18	97Y XL	BSW	25.0	10.4	9.0	9.5	10.5	9/32	1609	50
225/35ZR19	88Y XL	BSW	25.2	8.9	7.5	8.0	9.0	9/32	1235	50
225/40ZR19	93Y XL	BSW	26.1	8.9	7.5	8.0	9.0	9/32	1433	50

VICTRA | SPORT 5 CONTINUED

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
235/35ZR19	91Y XL	BSW	25.5	9.3	8.0	8.5	9.5	9/32	1356	50
235/40ZR19	96Y XL	BSW	26.4	9.3	8.0	8.5	9.5	9/32	1565	50
245/35ZR19	93Y XL	BSW	25.8	9.6	8.0	8.5	9.5	9/32	1433	50
245/40ZR19	98Y XL	BSW	26.7	9.6	8.0	8.5	9.5	9/32	1653	50
245/45ZR19	102Y XL	BSW	27.7	9.6	7.5	8.0	9.0	9/32	1874	50
255/35ZR19	96Y XL	BSW	26.0	10.0	8.5	9.0	10.0	9/32	1565	50
255/40ZR19	100Y XL	BSW	27.0	10.0	8.5	9.0	10.0	9/32	1764	50
255/45ZR19	104Y XL	BSW	28.0	10.0	8.0	8.5	9.5	9/32	1984	50
265/35ZR19	98Y XL	BSW	26.3	10.4	9.0	9.5	10.5	9/32	1653	50
275/35ZR19	100Y XL	BSW	26.6	10.8	9.0	9.5	11.0	8/32	1764	50
235/65ZR17	104W	BSW	29.1	9.3	6.5	7.0	8.5	TBD	1984	51
235/50ZR18	97Y	BSW	27.3	9.3	6.5	7.5	8.5	TBD	1609	51
235/55ZR18	100Y	BSW	28.1	9.3	6.5	7.5	8.5	TBD	1764	51
235/65ZR18	106W	BSW	30.0	9.3	6.5	7.0	8.5	TBD	2094	51
255/55ZR18	109Y XL	BSW	29.0	10.0	7.0	8.0	9.0	TBD	2271	50
235/50ZR19	99W	BSW	28.3	9.3	6.5	7.5	8.5	TBD	1709	51
235/55ZR19	101Y	BSW	29.2	9.3	6.5	7.5	8.5	TBD	1819	51
255/45ZR19	104Y XL	BSW	28.1	10.0	8.0	8.5	9.5	TBD	1984	50
255/50ZR19	107Y XL	BSW	29.1	10.0	7.0	8.0	9.0	TBD	2149	50
255/55ZR19	111Y XL	BSW	29.0	10.0	7.0	8.0	9.0	TBD	2403	50
265/50ZR19	110Y XL	BSW	29.5	10.4	7.5	8.5	9.5	TBD	2337	50
275/45ZR19	108Y XL	BSW	28.8	10.8	8.5	9.0	10.5	TBD	2205	50
275/55ZR19	111Y	BSW	22.2	10.8	7.5	8.5	9.5	TBD	2403	50
235/55ZR20	102W	BSW	30.2	9.3	6.5	7.5	8.5	TBD	1874	51
245/45ZR20	103W XL	BSW	28.7	9.6	7.5	8.0	9.0	TBD	1929	50
255/45ZR20	105Y XL	BSW	29.1	10.0	8.0	8.5	9.5	TBD	2039	50
255/50ZR20	109Y XL	BSW	30.1	10.0	7.0	8.0	9.0	TBD	2271	50
255/55ZR20	110Y XL	BSW	31.0	10.0	7.0	8.0	9.0	TBD	2337	50
265/45ZR20	104Y	BSW	29.4	10.4	8.5	9.0	10.0	TBD	1984	51
275/40ZR20	106Y XL	BSW	28.7	10.8	9.0	9.5	11.0	TBD	2094	50
275/45ZR20	110Y XL	BSW	29.8	10.8	8.5	9.0	10.5	TBD	2337	50
295/40ZR20	110Y XL	BSW	29.3	11.6	10.0	10.5	11.5	TBD	2337	50
315/35ZR20	110W XL	BSW	28.7	12.4	10.5	11.0	12.5	TBD	2337	50
275/45ZR21	110Y XL	BSW	30.7	10.8	8.5	9.0	10.5	TBD	2337	50
295/35ZR21	107Y XL	BSW	29.1	11.6	10.0	10.5	11.5	TBD	2149	50



VICTRA | Z3



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
165/50R15	72V	BSW	21.7	6.5	4.5	5.0	6.0	10/32	783	44
195/45ZR15	78W	BSW	21.9	7.6	6.0	6.5	7.5	9/32	937	51
195/50R15	86V XL	BSW	22.8	7.7	5.5	6.0	7.0	9/32	1168	50
195/55R15	85V	BSW	23.4	7.6	5.5	6.0	7.0	9/32	1135	44
205/50R15	89V XL	BSW	23.2	8.2	5.5	6.5	7.5	10/32	1279	50
205/55R15	88V	BSW	23.8	8.2	5.5	6.5	7.5	9/32	1235	44
195/45R16	84V XL	BSW	23.1	7.4	6.0	6.5	7.5	9/32	1102	50
195/50R16	88V XL	BSW	23.7	7.8	5.5	6.0	7.0	9/32	1235	50
195/55R16	91V	BSW	24.5	7.6	5.5	6.0	7.0	9/32	1356	50
205/40R16	83W XL	BSW	22.4	8.4	7.0	7.5	8.0	9/32	1074	50
205/45R16	87W XL	BSW	23.4	8.1	6.5	7.0	7.5	9/32	1201	50
205/50R16	91W XL	BSW	24.2	8.2	5.5	6.5	7.5	9/32	1356	50
205/55R16	94W XL	BSW	24.9	8.2	5.5	6.5	7.5	9/32	1477	50
215/40R16	86W XL	BSW	22.8	8.6	7.0	7.5	8.5	9/32	1168	50
215/55R16	97W XL	BSW	25.3	8.7	6.0	7.0	7.5	9/32	1609	50
225/45R16	93W XL	BSW	24.1	9.0	7.0	7.5	8.5	9/32	1433	50
225/50R16	96W XL	BSW	24.8	9.0	6.0	7.0	8.0	9/32	1565	50
225/55ZR16	99W XL	BSW	25.7	9.0	6.0	7.0	8.0	10/32	1709	50
205/40R17	84W XL	BSW	23.5	8.2	7.0	7.5	8.0	10/32	1102	50
205/45R17	88W XL	BSW	24.3	8.0	6.5	7.0	7.5	9/32	1235	50
205/50R17	93W XL	BSW	25.3	8.3	5.5	6.5	7.5	9/32	1432	50
215/40R17	87W XL	BSW	23.9	8.6	7.0	7.5	8.5	9/32	1201	50
215/45R17	91W XL	BSW	24.7	8.4	7.0	7.0	8.0	9/32	1356	50
215/50R17	91W	BSW	25.5	8.7	6.0	7.0	7.5	9/32	1356	51
215/55ZR17	98W XL	BSW	26.4	8.6	6.0	7.0	7.5	10/32	1653	50
225/45R17	94W XL	BSW	25.1	8.7	7.0	7.5	8.5	9/32	1477	50
225/55R17	101W XL	BSW	26.8	8.8	6.0	7.0	8.0	9/32	1819	50
235/40R17	94W XL	BSW	24.4	9.7	8.0	8.5	9.5	10/32	1477	50
235/45R17	97W XL	BSW	25.4	9.2	7.5	8.0	9.0	10/32	1609	50
245/40R17	95W XL	BSW	24.6	9.7	8.0	8.5	9.5	10/32	1521	50
245/45R17	99W XL	BSW	25.7	9.5	7.5	8.0	9.0	10/32	1709	50
255/40R17	98W XL	BSW	25.0	10.2	8.5	9.0	10.0	10/32	1653	50
275/40R17	98W	BSW	25.7	10.7	9.0	9.5	11.0	10/32	1653	51
225/40R18	92W XL	BSW	25.2	9.0	7.5	8.0	9.0	10/32	1389	50
225/45R18	95W XL	BSW	26.1	8.8	7.0	7.5	8.5	9/32	1521	50
235/40R18	95W XL	BSW	25.4	9.5	8.0	8.5	9.5	10/32	1521	50
235/50R18	101W XL	BSW	27.2	9.4	6.5	7.5	8.5	10/32	1819	50
245/40R18	97W XL	BSW	25.7	9.6	8.0	8.5	9.5	10/32	1609	50
245/45R18	100W XL	BSW	26.7	9.5	7.5	8.0	9.0	10/32	1764	50
255/45R18	103W XL	BSW	27.1	10.1	8.0	8.5	9.5	10/32	1929	50
265/35R18	97W XL	BSW	25.3	10.7	9.0	9.5	10.5	10/32	1609	50

XL - Extra Load; BSW - Black Sidewall

VICTRA | Z4S

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
205/60R14	88W	BSW	23.7	8.1	5.5	6.0	7.5	10/32	1235	51
195/50R15	86V XL	BSW	22.7	7.7	5.5	6.0	7.0	10/32	1168	50
195/55R15	85V	BSW	23.8	7.7	5.5	6.0	7.0	10/32	1135	44
205/50R15	89V XL	BSW	23.1	8.1	5.5	6.5	7.5	10/32	1290	50
225/50R15	95V XL	BSW	23.9	8.9	6.0	7.0	8.0	10/32	1521	50
225/60R15	96W	BSW	25.6	8.9	6.0	6.5	8.0	10/32	1565	51
185/55R16	83V	BSW	24.4	7.3	5.0	6.0	6.5	10/32	1074	44
195/50R16	88V XL	BSW	23.7	7.7	5.5	6.0	7.0	10/32	1235	50
195/55R16	91V XL	BSW	24.5	7.7	5.5	6.0	7.0	10/32	1356	50
205/40ZR16	83W XL	BSW	22.4	8.1	7.0	7.5	8.0	10/32	1074	50
205/45ZR16	87W XL	BSW	23.4	8.1	6.5	7.0	7.5	10/32	1201	50
205/50R16	91V XL	BSW	24.1	8.1	5.5	6.5	7.5	10/32	1356	50
205/55R16	94V XL	BSW	24.9	8.1	5.5	6.5	7.5	10/32	1477	50
215/45R16	86W	BSW	23.6	8.5	7.0	7.0	8.0	10/32	1168	44
215/55R16	97V XL	BSW	25.3	8.5	6.0	7.0	7.5	10/32	1609	50
225/50R16	96V XL	BSW	24.9	8.9	6.0	7.0	8.0	10/32	1565	50
225/55R16	99V XL	BSW	25.8	8.9	6.0	7.0	8.0	10/32	1709	50
245/50R16	97V	BSW	25.7	9.6	7.0	7.5	8.5	10/32	1609	44
195/40ZR17	81W XL	BSW	25.5	7.7	6.5	7.0	7.5	10/32	1019	50
195/45ZR17	85W XL	BSW	25.6	7.7	6.0	6.5	7.5	10/32	1135	50
205/40ZR17	84W XL	BSW	23.5	8.1	7.0	7.5	8.0	10/32	1102	50
205/45ZR17	88W XL	BSW	24.3	8.1	6.5	7.0	7.5	10/32	1235	50
205/50ZR17	93W XL	BSW	25.1	8.1	5.5	6.5	7.5	10/32	1433	50
215/40ZR17	87W XL	BSW	23.8	8.5	7.0	7.5	8.5	10/32	1201	50
215/45ZR17	91W XL	BSW	24.8	8.5	7.0	7.0	8.0	10/32	1356	50
215/50ZR17	95W XL	BSW	25.6	8.5	6.0	7.0	7.5	10/32	1521	50
225/45ZR17	94W XL	BSW	25.1	8.9	7.0	7.5	8.5	10/32	1477	50
225/50ZR17	98W XL	BSW	25.8	8.9	6.0	7.0	8.0	10/32	1653	50
225/55R17	101W XL	BSW	26.6	9.4	6.0	7.0	8.0	10/32	1819	50
225/55ZR17	101W XL	BSW	26.8	8.9	6.0	7.0	8.0	10/32	1819	50
235/45ZR17	97W XL	BSW	25.4	9.3	7.5	8.0	9.0	10/32	1609	50
235/50ZR17	100W XL	BSW	27.3	9.3	6.5	7.5	8.5	10/32	1764	50
235/55ZR17	103W XL	BSW	27.4	9.3	6.5	7.5	8.5	10/32	1929	50
245/40ZR17	95W XL	BSW	24.7	9.6	8.0	8.5	9.5	10/32	1521	50
245/45ZR17	99W XL	BSW	25.7	9.6	7.5	8.0	9.0	10/32	1708	50
255/40ZR17	98W XL	BSW	25.0	10.0	8.5	9.0	10.0	10/32	1653	50
215/35ZR18	84W XL	BSW	23.9	8.5	7.0	7.5	8.5	10/32	1102	50
225/40ZR18	92W XL	BSW	25.2	8.9	7.5	8.0	9.0	10/32	1389	50
225/45ZR18	95W XL	BSW	27.8	8.9	7.0	7.5	8.5	10/32	1521	50
235/40ZR18	95W XL	BSW	25.4	9.3	8.0	8.5	9.5	10/32	1521	50



VICTRA | Z4S CONTINUED



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
235/50ZR18	101W XL	BSW	28.3	9.3	6.5	7.5	8.5	10/32	1819	50
235/55ZR18	104W XL	BSW	28.4	9.3	6.5	7.5	8.5	10/32	1984	50
235/60ZR18	107W XL	BSW	28.5	9.3	6.5	7.0	8.5	10/32	2149	50
245/40ZR18	97W XL	BSW	25.7	9.6	8.0	8.5	9.5	10/32	1609	50
245/45ZR18	100W XL	BSW	28.5	9.6	7.5	8.0	9.0	10/32	1764	50
245/60R18	105V	BSW	29.6	9.6	7.0	7.0	8.5	10/32	2039	44
255/35ZR18	94W XL	BSW	28.7	10.0	8.5	9.0	10.0	10/32	1477	50
255/55ZR18	109W XL	BSW	29.1	10.0	7.0	8.0	9.0	10/32	2270	50
265/35ZR18	97W XL	BSW	25.4	10.4	9.0	9.5	10.5	10/32	1609	50
215/35ZR19	85W XL	BSW	25.0	8.5	7.0	7.5	8.5	10/32	1135	50
225/35ZR19	88W XL	BSW	25.3	8.9	7.5	8.0	9.0	10/32	1235	50
225/55ZR19	99W	BSW	28.9	8.9	6.0	7.0	8.0	10/32	1709	51
235/35ZR19	91W XL	BSW	29.0	9.3	8.0	8.5	9.5	10/32	1356	50
245/35ZR19	93W XL	BSW	29.3	9.6	8.0	8.5	9.5	10/32	1433	50
245/40ZR19	98W XL	BSW	29.4	9.6	8.0	8.5	9.5	10/32	1653	50
255/50ZR19	107W XL	BSW	30.0	10.0	7.0	8.0	9.0	10/32	2149	50
255/55ZR19	111W XL	BSW	30.1	10.0	7.0	8.0	9.0	10/32	2403	50
275/30ZR19	96W XL	BSW	30.4	10.8	9.0	9.5	10.0	10/32	1565	50
275/35ZR19	100W XL	BSW	30.5	10.8	9.0	9.5	11.0	10/32	1764	50
285/45R19	111V XL	BSW	29.1	11.2	9.0	9.5	10.5	10/32	2403	50
225/30ZR20	85W XL	BSW	25.4	8.9	8.0	8.0	8.0	10/32	1135	50
225/35ZR20	90W XL	BSW	26.2	8.9	7.5	8.0	9.0	10/32	1323	50
235/35ZR20	92W XL	BSW	30.0	9.3	8.0	8.5	9.5	10/32	1389	50
245/35ZR20	95W XL	BSW	26.5	9.6	8.0	8.5	9.5	10/32	1521	50
245/40ZR20	99W XL	BSW	27.7	9.6	8.0	8.5	9.5	10/32	1709	50
245/45R20	99W	BSW	28.7	9.6	7.5	8.0	9.0	10/32	1709	51
245/50ZR20	102W	BSW	29.8	9.6	7.0	7.5	8.5	10/32	1874	51
255/35ZR20	97W XL	BSW	27.0	10.0	8.5	9.0	10.0	10/32	1609	50
255/45R20	105V XL	BSW	29.1	10.0	8.0	8.5	9.5	11/32	2039	50
255/50ZR20	109W XL	BSW	30.2	10.0	7.0	8.0	9.0	10/32	2271	50
255/55ZR20	110W XL	BSW	31.1	10.0	7.0	8.0	9.0	10/32	2337	50
275/30ZR20	97W XL	BSW	31.4	10.8	9.0	9.5	10.0	10/32	1609	50
275/35ZR20	102W XL	BSW	31.5	10.8	9.0	9.5	11.0	10/32	1874	50
275/40R20	106V XL	BSW	28.7	10.8	9.0	9.5	11.0	11/32	2094	50
275/45R20	110V XL	BSW	29.8	10.8	8.5	9.0	10.5	11/32	2337	50
275/55R20	117V XL	BSW	31.9	10.8	7.5	8.5	9.5	11/32	2833	50
285/50R20	116V XL	BSW	31.3	11.2	8.0	9.0	10.0	11/32	2756	50
315/35ZR20	110W XL	BSW	28.8	12.4	10.5	11.0	12.5	11/32	2337	50
245/30ZR22	92W XL	BSW	27.8	9.6	8.0	8.5	9.0	10/32	1389	50
265/35ZR22	102V XL	BSW	29.4	10.4	9.0	9.5	10.5	10/32	1874	50

VICTRA | Z4S CONTINUED

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
265/40R22	106V XL	BSW	30.4	10.4	9.0	9.5	10.5	11/32	2094	50
285/35R22	106V XL	BSW	33.9	11.2	9.5	10.0	11.0	10/32	2094	50
285/45R22	114V XL	BSW	34.1	11.2	9.0	9.5	10.5	10/32	2601	50
305/40R22	114V XL	BSW	31.6	12.0	10.0	11.0	12.0	11/32	2601	50
305/45R22	118V XL	BSW	32.8	12.0	9.5	10.0	11.5	11/32	2910	50
255/30ZR24	97W XL	BSW	30.1	10.0	8.5	9.0	9.5	10/32	1609	50
295/35R24	110V XL	BSW	32.1	11.6	10.0	10.5	11.5	11/32	2337	50
305/35ZR24	112V XL	BSW	32.6	12.0	10.0	11.0	12.0	11/32	2469	50

VICTRA | S11

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
195/50R15	82V	BSW	22.8	7.9	5.5	6.0	7.0	10/32	1047	44
185/55R15	86V XL	BSW	23.1	7.5	5.0	6.0	6.5	10/32	1168	50
195/55R15	85V	BSW	23.4	7.8	5.5	6.0	7.0	10/32	1135	44
195/60R15	88V	BSW	24.4	7.9	5.5	6.0	7.0	10/32	1235	44
195/65R15	91V	BSW	25.1	8.0	5.5	6.0	7.0	10/32	1356	44
205/65R15	95H	BSW	25.5	8.2	5.5	6.0	7.5	10/32	1521	44
205/50R16	87W	BSW	24.1	8.2	5.5	6.5	7.5	10/32	1201	51
205/55R16	94W XL	BSW	24.8	8.2	5.5	6.5	7.5	10/32	1477	50
225/55R16	95W	BSW	25.7	9.0	6.0	7.0	8.0	10/32	1521	51
215/60R16	95V	BSW	26.3	8.7	6.0	6.5	7.5	10/32	1521	44
225/60R16	98V	BSW	26.7	8.9	6.0	6.5	8.0	10/32	1653	44
215/65R16	98H	BSW	27.1	8.7	6.0	6.5	7.5	10/32	1653	44
215/45R17	91W XL	BSW	24.7	8.2	7.0	7.0	8.0	10/32	1356	50
225/45R17	94W XL	BSW	25.0	8.7	7.0	7.5	8.5	10/32	1477	50
235/45R17	97W XL	BSW	25.3	9.2	7.5	8.0	9.0	10/32	1609	50
245/45R17	99W XL	BSW	25.7	9.4	7.5	8.0	9.0	10/32	1709	50
205/50R17	93W XL	BSW	25.3	8.2	5.5	6.5	7.5	10/32	1433	50
225/50R17	98W XL	BSW	25.9	8.9	6.0	7.0	8.0	10/32	1653	50
235/50R17	100W XL	BSW	26.3	9.5	6.5	7.5	8.5	10/32	1764	50
215/55R17	94W	BSW	26.3	8.7	6.0	7.0	7.5	10/32	1477	51
225/40R18	92W XL	BSW	25.3	8.8	7.5	8.0	9.0	10/32	1389	50
235/40R18	95W XL	BSW	25.4	9.5	8.0	8.5	9.5	10/32	1521	50
245/40R18	97W XL	BSW	25.8	9.6	8.0	8.5	9.5	10/32	1609	50
225/45R18	95W XL	BSW	26.1	8.7	7.0	7.5	8.5	10/32	1521	50
245/45R18	100W XL	BSW	26.7	9.4	7.5	8.0	9.0	10/32	1764	50
245/35R19	93W XL	BSW	25.9	9.6	8.0	8.5	9.5	10/32	1433	50
245/40R19	98W XL	BSW	26.8	9.6	8.0	8.5	9.5	10/32	1653	50



PREMITRA | HPS



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
195/50R15	86V XL	BSW	22.7	7.7	5.5	6.0	7.0	10/32	1168	50
195/55R15	85V	BSW	23.5	7.7	5.5	6.0	7.0	10/32	1135	44
195/60R15	88V	BSW	24.3	7.7	5.5	6.0	7.0	10/32	1235	44
195/65R15	95V XL	BSW	25.0	7.7	5.5	6.0	7.0	10/32	1521	50
205/60R15	91H	BSW	24.7	8.3	5.5	6.0	7.5	10/32	1356	44
225/60R15	96V	BSW	25.6	9.0	6.0	6.5	8.0	10/32	1565	44
185/55R15	83V	BSW	24.0	7.3	5.0	6.0	6.5	10/32	1074	44
195/45R16	84V XL	BSW	22.9	7.7	6.0	6.5	7.5	10/32	1102	50
195/50R16	88V XL	BSW	23.7	7.7	5.5	6.0	7.0	10/32	1235	50
195/55R16	91V XL	BSW	24.5	7.7	5.5	6.0	7.0	10/32	1356	50
195/60R16	89V	BSW	25.3	8.0	5.5	6.0	7.0	10/32	1279	44
205/45ZR16	87W XL	BSW	23.2	8.1	6.5	7.0	7.5	10/32	1201	50
205/50ZR16	91W XL	BSW	24.1	8.1	5.5	6.5	7.5	10/32	1356	50
205/55ZR16	94W XL	BSW	24.9	8.1	5.5	6.5	7.5	10/32	1477	50
205/60R16	96V XL	BSW	25.7	8.1	5.5	6.0	7.5	10/32	1565	50
205/60R16	96W XL	BSW	25.7	8.3	5.5	6.0	7.5	10/32	1565	50
215/45R16	90V XL	BSW	23.6	8.5	7.0	7.0	8.0	10/32	1323	50
215/55R16	93V	BSW	25.4	8.5	6.0	7.0	7.5	10/32	1433	44
215/55ZR16	97W XL	BSW	25.4	8.1	6.0	7.0	7.5	10/32	1609	50
215/60ZR16	99W XL	BSW	26.2	8.5	6.0	6.5	7.5	10/32	1709	50
215/65R16	98V	BSW	27.0	8.5	6.0	6.5	7.5	10/32	1653	44
225/50ZR16	92W	BSW	24.9	8.9	6.0	7.0	8.0	10/32	1389	51
225/55R16	95V	BSW	25.8	8.9	6.0	7.0	8.0	10/32	1521	44
225/55ZR16	99W XL	BSW	25.8	8.9	6.0	7.0	8.0	10/32	1709	50
225/60R16	98V	BSW	26.6	8.9	6.0	6.5	8.0	10/32	1653	44
205/40ZR17	84W XL	BSW	23.5	8.1	7.0	7.5	8.0	10/32	1102	50
205/45ZR17	88W XL	BSW	24.3	8.1	6.5	7.0	7.5	10/32	1235	50
205/50ZR17	93W XL	BSW	25.1	8.1	5.5	6.5	7.5	10/32	1433	50
205/55R17	95V XL	BSW	26.0	8.1	5.5	6.5	7.5	10/32	1521	50
215/40ZR17	87W XL	BSW	23.8	8.5	7.0	7.5	8.5	10/32	1201	50
215/45ZR17	91W XL	BSW	24.6	8.5	7.0	7.0	8.0	10/32	1356	50
215/50ZR17	95W XL	BSW	25.4	8.5	6.0	7.0	7.5	10/32	1521	50
215/55ZR17	98W XL	BSW	26.4	8.5	6.0	7.0	7.5	10/32	1653	50
215/60R17	96H	BSW	27.2	8.5	6.0	6.5	7.5	10/32	1565	44
225/45ZR17	91W	BSW	25.0	8.9	7.0	7.5	8.5	10/32	1356	51
225/50ZR17	98W XL	BSW	25.9	8.9	6.0	7.0	8.0	10/32	1653	50
225/55ZR17	101W XL	BSW	26.9	8.9	6.0	7.0	8.0	10/32	1819	50
225/60R17	99V	BSW	27.6	8.9	6.0	6.5	8.0	10/32	1709	44
235/45ZR17	97W XL	BSW	25.4	9.3	7.5	8.0	9.0	10/32	1609	50
235/50R17	96V	BSW	26.3	9.3	6.5	7.5	8.5	10/32	1565	44

PREMITRA | HPS CONTINUED

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
235/55ZR17	103W XL	BSW	27.2	9.3	6.5	7.5	8.5	10/32	1929	50
245/45ZR17	99W XL	BSW	25.7	9.7	7.5	8.0	9.0	10/32	1709	50
215/50R18	92V	BSW	26.5	8.9	6.0	7.0	7.5	10/32	1389	44
215/55R18	99V XL	BSW	27.3	8.5	6.0	7.0	7.5	10/32	1709	50
225/40ZR18	92W XL	BSW	25.0	8.9	7.5	8.0	9.0	10/32	1389	50
225/45ZR18	95W XL	BSW	25.9	8.9	7.0	7.5	8.5	10/32	1521	50
225/55R18	98V	BSW	27.8	8.9	6.0	7.0	8.0	10/32	1653	44
235/40ZR18	95W XL	BSW	25.4	9.2	8.0	8.5	9.5	10/32	1521	50
235/45ZR18	98W XL	BSW	26.3	9.3	7.5	8.0	9.0	10/32	1653	50
235/50R18	97V	BSW	27.3	9.5	6.5	7.5	8.5	10/32	1609	44
235/50ZR18	101W XL	BSW	27.3	9.3	6.5	7.5	8.5	10/32	1819	50
245/40ZR18	97W XL	BSW	25.7	9.6	8.0	8.5	9.5	10/32	1609	50
245/45ZR18	100W XL	BSW	26.6	9.6	7.5	8.0	9.0	10/32	1764	50
245/50ZR18	104W XL	BSW	27.6	9.6	7.0	7.5	8.5	10/32	1984	50
255/35ZR18	94W XL	BSW	25.0	10.0	8.5	9.0	10.0	10/32	1477	50
255/45ZR18	99W	BSW	27.0	10.0	8.0	8.5	9.5	10/32	1709	51

ESCAPADE | MA-T1

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
165/65R13	77T	BSW	21.5	6.6	4.5	5.0	6.0	11/32	908	44
165/70R13	79T	BSW	22.2	6.6	4.0	5.0	5.5	11/32	963	44
P175/70R13	82T	BSW	22.7	6.9	4.5	5.0	6.0	12/32	1047	44
P185/70R13	86T	BSW	23.2	7.3	4.5	5.5	6.0	12/32	1168	44
185/60R14	82H	BSW	22.8	7.5	5.0	5.5	6.5	11/32	1047	44
P195/60R14	86T	BSW	23.2	7.7	5.5	6.0	7.0	12/32	1168	44
P185/65R14	86T	BSW	23.5	7.3	5.0	5.5	6.5	12/32	1168	44
P185/70R14	88T	BSW	24.3	7.3	4.5	5.5	6.0	12/32	1235	44
P195/70R14	91T	BSW	24.8	7.7	5.0	6.0	6.5	12/32	1356	44
P205/70R14	95T	BSW	25.4	8.1	5.0	6.0	7.0	12/32	1521	44
P195/60R15	88T	BSW	24.2	7.7	5.5	6.0	7.0	12/32	1235	44
P205/60R15	91T	BSW	24.7	8.1	5.5	6.0	7.5	12/32	1356	44
P215/60R15	94T	BSW	25.2	8.5	6.0	6.5	7.5	12/32	1477	44
P195/65R15	91T	BSW	25.0	7.7	5.5	6.0	7.0	12/32	1356	44
P205/65R15	94T	BSW	25.5	8.1	5.5	6.0	7.5	12/32	1477	44
P205/70R15	96T	RWW	26.3	8.1	5.0	6.0	7.0	12/32	1565	44
P205/70R15	96T	BSW	26.3	8.1	5.0	6.0	7.0	12/32	1565	44
P215/70R15	98T	BSW	26.9	8.5	5.5	6.5	7.0	12/32	1653	44



ESCAPADE | MA-T1 CONTINUED



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
P215/70R15	98T	RWW	26.9	8.5	5.5	6.5	7.0	12/32	1653	44
P205/55R16	91V	BSW	24.9	8.1	5.5	6.5	7.5	12/32	1356	44
215/55R16	97H XL	BSW	25.2	8.5	6.0	7.0	7.5	12/32	1609	50
225/55R16	99V XL	BSW	25.7	8.9	6.0	7.0	8.0	12/32	1709	50
205/60R16	92V	BSW	25.8	8.1	5.5	6.0	7.5	12/32	1389	44
P215/60R16	95H	BSW	26.1	8.5	6.0	6.5	7.5	12/32	1521	44
P215/60R16	95T	BSW	26.1	8.5	6.0	6.5	7.5	12/32	1521	44
P225/60R16	98T	BSW	26.8	8.9	6.0	6.5	8.0	12/32	1653	44
215/55R17	94V	BSW	26.3	8.5	6.0	7.0	7.5	12/32	1477	44
225/55R17	101H XL	BSW	26.9	8.9	6.0	7.0	8.0	12/32	1819	50
P215/60R17	96T	BSW	27.2	8.8	6.0	6.5	7.5	12/32	1565	44
P225/60R17	99T	BSW	27.6	8.9	6.0	6.5	8.0	12/32	1709	44
P215/65R17	99T	BSW	28.0	8.5	6.0	6.5	7.5	12/32	1709	44
225/55R18	98H	BSW	27.8	8.9	6.0	7.0	8.0	12/32	1653	44
P225/60R18	100V	BSW	28.6	8.9	6.0	6.5	8.0	12/32	1764	44

MECOTRA | ME3



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
145/60R13	66T	BSW	21.0	6.1	4.0	4.5	5.0	9/32	661	44
145/70R13	71T	BSW	21.0	6.1	3.5	4.5	5.0	9/32	761	44
145/80R13	75T	BSW	22.1	5.7	3.5	4.0	5.0	9/32	653	44
155/65R13	73T	BSW	20.8	6.3	4.5	4.5	5.5	9/32	805	44
155/70R13	75T	BSW	21.6	6.1	4.0	4.5	5.0	9/32	853	44
155/80R13	79T	BSW	22.8	6.1	4.0	4.5	5.0	9/32	963	44
165/65R13	77T	BSW	21.3	6.5	4.5	5.0	6.0	9/32	909	44
165/70R13	79T	BSW	22.2	6.7	4.0	5.0	5.5	9/32	963	44
165/80R13	83T	BSW	23.4	6.5	4.0	4.5	5.5	9/32	1074	44
175/60R13	77H	BSW	21.3	7.2	5.0	5.0	6.0	9/32	908	44
175/65R13	80T	BSW	21.9	7.2	5.0	5.0	6.0	9/32	992	44
175/70R13	82T	BSW	22.7	6.8	4.5	5.0	6.0	9/32	1047	44
175/70R13	82H	BSW	22.7	6.8	4.5	5.0	6.0	9/32	1047	44
185/70R13	86H	BSW	23.3	7.4	4.5	5.5	6.0	9/32	1168	44
205/60R13	86H	BSW	22.7	8.5	5.5	6.0	7.5	9/32	1168	44
155/65R14	75T	BSW	21.9	6.0	4.5	4.5	5.5	9/32	853	44
155/70R14	77T	BSW	22.7	6.1	4.0	4.5	5.0	9/32	908	44
165/60R14	75H	BSW	21.9	6.6	4.5	5.0	6.0	9/32	853	44
165/60R14	75T	BSW	21.9	6.6	4.5	5.0	6.0	9/32	853	44
165/65R14	79T	BSW	22.3	6.4	4.5	5.0	6.0	9/32	963	44

MECOTRA | ME3 CONTINUED

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
165/65R14	83H XL	BSW	22.3	6.5	4.5	5.0	6.0	9/32	1074	50
165/70R14	81T	BSW	23.2	6.7	4.0	5.0	5.5	9/32	1019	44
165/70R14	85T XL	BSW	23.2	6.7	4.0	5.0	5.5	9/32	1135	50
175/60R14	79H	BSW	22.4	6.9	5.0	5.0	6.0	9/32	963	44
175/65R14	82H	BSW	23.0	6.9	5.0	5.0	6.0	9/32	1047	44
175/65R14	86H XL	BSW	23.0	6.9	5.0	5.0	6.0	9/32	1168	50
175/65R14	82T	BSW	23.0	6.9	5.0	5.0	6.0	9/32	1047	44
175/65R14	86T XL	BSW	23.0	6.9	5.0	5.0	6.0	9/32	1168	50
175/70R14	84H	BSW	23.7	7.0	4.5	5.0	6.0	9/32	1102	44
175/70R14	84T	BSW	23.7	7.0	4.5	5.0	6.0	9/32	1102	44
175/70R14	88T XL	BSW	23.7	7.0	4.5	5.0	6.0	9/32	1235	50
175/80R14	88T	BSW	25.0	7.1	4.5	5.0	6.0	9/32	1235	44
185/55R14	80V	BSW	22.1	7.6	5.0	6.0	6.5	9/32	992	44
185/60R14	82H	BSW	22.9	7.3	5.0	5.5	6.5	9/32	1047	44
185/60R14	82T	BSW	22.9	7.3	5.0	5.5	6.5	9/32	1047	44
185/65R14	86H	BSW	23.4	7.3	5.0	5.5	6.5	9/32	1168	44
185/65R14	86T	BSW	23.4	7.3	5.0	5.5	6.5	9/32	1168	44
185/70R14	88H	BSW	24.3	7.4	4.5	5.5	6.0	9/32	1235	44
185/70R14	88T	BSW	24.3	7.4	4.5	5.5	6.0	9/32	1235	44
185/80R14	91T	BSW	25.7	7.3	TBD	6.0	TBD	9/32	1356	44
195/60R14	86H	BSW	23.3	7.8	5.5	6.0	7.0	9/32	1168	44
195/65R14	89H	BSW	23.9	7.8	5.5	6.0	7.0	9/32	1279	44
195/70R14	91T	BSW	24.9	7.8	5.0	6.0	6.5	9/32	1356	44
205/70R14	95V	BSW	25.4	8.4	5.0	6.0	7.0	9/32	1521	44
135/70R15	70T	BSW	22.5	5.6	TBD	4.0	TBD	9/32	739	44
135/80R15	73T	BSW	23.6	5.2	3.5	3.5	4.5	9/32	805	44
145/65R15	72T	BSW	22.4	5.8	4.0	4.5	5.0	9/32	783	44
155/60R15	74T	BSW	22.4	6.1	4.5	4.5	5.5	9/32	827	44
165/60R15	77H	BSW	22.9	6.6	4.5	5.0	6.0	9/32	908	44
165/60R15	81T XL	BSW	23.0	6.6	4.5	5.0	6.0	9/32	1019	50
165/65R15	81H	BSW	23.4	6.5	4.5	5.0	6.0	9/32	1019	44
165/80R15	87T	BSW	25.5	6.5	4.0	4.5	5.5	9/32	1201	44
175/55R15	77T	BSW	22.6	7.1	5.0	5.5	6.0	9/32	908	44
175/60R15	81H	BSW	23.4	6.8	5.0	5.0	6.0	9/32	1019	44
175/65R15	84H	BSW	24.0	6.9	5.0	5.0	6.0	9/32	1102	44
175/65R15	84T	BSW	24.0	6.9	5.0	5.0	6.0	9/32	1102	44
185/55R15	82H	BSW	23.1	7.7	5.0	6.0	6.5	9/32	1047	44
185/60R15	84H	BSW	23.9	7.4	5.0	5.5	6.5	9/32	1102	44
185/60R15	88H XL	BSW	23.9	7.4	5.0	5.5	6.5	9/32	1235	50
185/65R15	88H	BSW	24.4	7.4	5.0	5.5	6.5	9/32	1235	44
185/65R15	88T	BSW	24.4	7.4	5.0	5.5	6.5	9/32	1235	44



MECOTRA | ME3 CONTINUED



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
185/65R15	92T XL	BSW	24.4	7.4	5.0	5.5	6.5	9/32	1389	50
195/45R15	78V	BSW	21.9	7.6	6.0	6.5	7.5	9/32	937	44
195/50R15	82H	BSW	22.8	7.8	5.5	6.0	7.0	9/32	1047	44
195/55R15	85H	BSW	23.5	8.0	5.5	6.0	7.0	9/32	1135	44
195/55R15	85V	BSW	23.5	8.0	5.5	6.0	7.0	9/32	1135	44
195/60R15	88H	BSW	24.3	8.0	5.5	6.0	7.0	9/32	1235	44
195/60R15	88V	BSW	24.3	8.0	5.5	6.0	7.0	9/32	1235	44
195/65R15	91H	BSW	24.9	8.0	5.5	6.0	7.0	9/32	1356	44
195/65R15	95T XL	BSW	24.9	8.0	5.5	6.0	7.0	9/32	1521	50
195/65R15	91V	BSW	24.9	8.0	5.5	6.0	7.0	9/32	1356	44
205/55R15	88V	BSW	24.0	8.4	5.5	6.5	7.5	9/32	1235	44
205/60R15	91H	BSW	24.8	8.3	5.5	6.0	7.5	9/32	1356	44
205/60R15	91V	BSW	24.8	8.3	5.5	6.0	7.5	9/32	1356	44
205/65R15	94H	BSW	25.4	8.2	5.5	6.0	7.5	9/32	1477	44
205/65R15	99T XL	BSW	25.4	8.2	5.5	6.0	7.5	9/32	1709	50
205/65R15	94V	BSW	25.4	8.2	5.5	6.0	7.5	9/32	1477	44
205/70R15	96H	BSW	26.4	8.3	5.0	6.0	7.0	9/32	1565	44
215/65R15	96H	BSW	25.9	8.7	6.0	6.5	7.5	9/32	1565	44
175/60R16	82H	BSW	24.4	6.9	5.0	5.0	6.0	9/32	1047	44
185/50R16	81V	BSW	23.5	7.4	5.0	6.0	6.5	9/32	1019	44
185/55R16	83V	BSW	24.1	7.6	5.0	6.0	6.5	9/32	1074	44
185/60R16	86H	BSW	24.9	7.4	5.0	5.5	6.5	9/32	1168	44
195/55R16	87H	BSW	24.6	7.9	5.5	6.0	7.0	9/32	1201	44
195/55R16	91T XL	BSW	24.6	7.9	5.5	6.0	7.0	9/32	1356	50
195/55R16	87V	BSW	24.6	7.9	5.5	6.0	7.0	9/32	1201	44
195/60R16	89H	BSW	25.3	7.8	5.5	6.0	7.0	9/32	1279	44
205/55R16	91H	BSW	25.1	8.4	5.5	6.5	7.5	9/32	1356	44
205/55R16	94H XL	BSW	25.1	8.4	5.5	6.5	7.5	9/32	1477	50
205/55R16	91V	BSW	25.1	8.4	5.5	6.5	7.5	9/32	1356	44
205/60R16	92H	BSW	25.9	8.2	5.5	6.0	7.5	9/32	1389	44
205/60R16	96H XL	BSW	25.9	8.2	5.5	6.0	7.5	9/32	1565	50
205/60R16	92V	BSW	25.9	8.2	5.5	6.0	7.5	9/32	1389	44
215/55R16	97V XL	BSW	25.5	8.8	6.0	7.0	7.5	9/32	1609	50
215/60R16	95H	BSW	26.2	8.7	6.0	6.5	7.5	9/32	1521	44
215/60R16	99H XL	BSW	26.3	8.7	6.0	6.5	7.5	9/32	1709	50
215/60R16	95V	BSW	26.2	8.7	6.0	6.5	7.5	9/32	1521	44
195/55R20	95H XL	BSW	28.8	7.6	5.5	6.0	7.0	9/32	1521	50

i-ECO

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
165/65R13	77H	BSW	21.4	6.6	4.5	5.0	6.0	9/32	908	44
165/70R13	79H	BSW	22.1	6.5	4.0	5.0	5.5	9/32	963	44
175/70R13	82H	BSW	22.6	6.9	4.5	5.0	6.0	9/32	1047	44
185/60R14	82H	BSW	22.8	7.4	5.0	5.5	6.5	9/32	1047	44
185/65R14	86H	BSW	23.5	7.4	5.0	5.5	6.5	9/32	1168	44
195/60R14	86H	BSW	23.2	7.9	5.5	6.0	7.0	9/32	1168	44
175/65R15	84H	BSW	24.1	7.0	5.0	5.0	6.0	9/32	1102	44
185/60R15	84H	BSW	23.8	7.3	5.0	5.5	6.5	9/32	1102	44
185/65R15	88H	BSW	24.5	7.4	5.0	5.5	6.5	9/32	1235	44
195/55R15	85V	BSW	23.4	7.9	5.5	6.0	7.0	9/32	1135	44
195/60R15	88H	BSW	24.3	8.1	5.5	6.0	7.0	9/32	1235	44
195/65R15	91H	BSW	25.1	8.0	5.5	6.0	7.0	9/32	1356	44
205/60R15	91H	BSW	24.8	8.2	5.5	6.0	7.5	10/32	1356	44
205/65R15	94H	BSW	25.6	8.2	5.5	6.0	7.5	10/32	1477	44
195/55R16	87V	BSW	24.4	7.9	5.5	6.0	7.0	9/32	1201	44
205/55R16	91V	BSW	24.9	8.4	5.5	6.5	7.5	10/32	1356	44
205/60R16	92H	BSW	25.8	8.3	5.5	6.0	7.5	10/32	1389	44
215/60R16	95H	BSW	26.1	8.7	6.0	6.5	7.5	10/32	1521	44
225/60R16	98H	BSW	26.7	9.1	6.0	6.5	8.0	10/32	1653	44
235/60R16	100V	BSW	27.1	9.5	6.5	7.0	8.5	10/32	1764	44
215/50R17	91V	BSW	25.6	8.7	6.0	7.0	7.5	10/32	1356	44
215/55R17	94V	BSW	26.2	8.9	6.0	7.0	7.5	10/32	1477	44



MA-P3

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
155/70R12	73H	BSW	20.6	6.1	TBD	TBD	TBD	10/32	805	44
155/80R12	77H	BSW	21.8	6.2	TBD	TBD	TBD	10/32	908	44
165/70R12	77S	BSW	21.1	6.7	4.0	5.0	5.5	10/32	908	44
155/65R13	73T	BSW	20.9	6.1	4.5	4.5	5.5	9/32	805	44
155/70R13	75T	BSW	21.6	6.1	4.0	4.5	5.0	9/32	853	44
155/80R13	79T	BSW	22.8	6.3	4.0	4.5	5.0	9/32	963	44
165/65R13	77H	BSW	21.4	6.7	4.5	5.0	6.0	10/32	908	44
165/80R13	83S	RWW	25.1	7.9	4.0	4.5	5.5	9/32	1074	44
165/80R13	83T	BSW	23.4	6.5	4.0	4.5	5.5	9/32	1074	44
175/60R13	77H	BSW	28.5	8.8	5.0	5.0	6.0	9/32	908	44
175/70R13	82H	BSW	22.7	6.9	4.5	5.0	6.0	10/32	1047	44



MA-P3 CONTINUED



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
175/70R13	82T	RWW	28.5	8.8	4.5	5.0	6.0	10/32	1047	44
185/60R13	80V	BSW	21.8	7.3	5.0	5.5	6.5	10/32	992	44
185/70R13	86H	BSW	23.2	7.5	4.5	5.5	6.0	10/32	1168	44
205/60R13	86H	BSW	22.7	8.4	5.5	6.0	7.5	10/32	1168	44
215/50R13	84H	BSW	21.5	8.8	6.0	7.0	7.5	9/32	1102	44
175/65R14	82H	BSW	23.0	6.9	5.0	5.0	6.0	9/32	1047	44
175/70R14	84H	BSW	23.7	7.0	4.5	5.0	6.0	10/32	1102	44
175/80R14	88H	BSW	25.0	7.1	4.5	5.0	6.0	9/32	1235	44
185/60R14	82H	BSW	22.8	7.3	5.0	5.5	6.5	10/32	1047	44
185/65R14	86H	BSW	23.5	7.5	5.0	5.5	6.5	10/32	1168	44
185/70R14	88H	BSW	24.3	7.5	4.5	5.5	6.0	10/32	1235	44
185/70R14	88H	RWW	24.3	7.5	4.5	5.5	6.0	10/32	1235	44
185/80R14	91T	BSW	25.7	7.5	4.5	5.0	6.0	10/32	1356	44
195/70R14	91H	BSW	24.8	7.9	5.0	6.0	6.5	10/32	1356	44
205/60R14	88H	BSW	23.8	8.3	5.5	6.0	7.5	10/32	1235	44
205/70R14	95H	BSW	25.4	8.1	5.0	6.0	7.0	10/32	1521	44
205/75R14	95S	RWW	26.3	8.1	5.0	5.5	7.0	11/32	1521	44
165/80R15	87T	BSW	25.4	6.5	4.0	4.5	5.5	9/32	1202	44
185/55R15	82V	BSW	23.1	7.5	5.0	6.0	6.5	10/32	1047	44
185/60R15	88H XL	BSW	23.8	7.4	5.0	5.5	6.5	10/32	1235	50
185/65R15	88H	BSW	24.5	7.4	5.0	5.5	6.5	9/32	1235	44
185/65R15	92H XL	BSW	24.5	7.4	5.0	5.5	6.5	9/32	1389	50
195/55R15	85V	BSW	23.5	7.8	5.5	6.0	7.0	10/32	1135	44
195/60R15	88H	BSW	24.3	7.9	5.5	6.0	7.0	10/32	1235	44
195/65R15	91H	BSW	25.0	7.9	5.5	6.0	7.0	10/32	1356	44
195/65R15	95H XL	BSW	25.0	7.9	5.5	6.0	7.0	10/32	1521	50
205/60R15	91H	BSW	24.8	8.1	5.5	6.0	7.5	10/32	1356	44
205/65R15	95H	BSW	25.5	8.2	5.5	6.0	7.5	10/32	1521	44
205/70R15	96H	BSW	26.4	8.3	5.0	6.0	7.0	11/32	1565	44
205/70R15	96S	RWW	26.4	8.2	5.0	6.0	7.0	11/32	1565	44
205/75R15	97S	RWW	27.4	8.0	5.0	5.5	7.0	11/32	1609	44
215/65R15	96H	BSW	26.1	8.7	6.0	6.5	7.5	10/32	1565	44
215/70R15	98H	BSW	26.9	8.8	5.5	6.5	7.0	10/32	1653	44
215/70R15	98S	RWW	26.9	8.7	5.5	6.5	7.0	10/32	1653	44
215/75R15	100S	RWW	27.8	8.6	5.5	6.0	7.0	11/32	1764	44
225/70R15	100S	RWW	27.4	9.1	6.0	6.5	7.5	12/32	1764	44
225/75R15	102S	RWW	28.4	8.9	6.0	6.0	7.5	11/32	1874	44
235/75R15	105S	RWW	29.1	9.3	6.0	6.5	8.0	11/32	2039	44
205/55R16	91V	BSW	25.0	8.3	5.5	6.5	7.5	10/32	1356	44
205/65R16	95H	BSW	26.5	8.2	5.5	6.0	7.5	10/32	1521	44

XL - Extra Load; BSW - Black Sidewall; RWW - Raised White Wall

MA-P3 CONTINUED

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
215/60R16	99H XL	BSW	26.3	8.7	6.0	6.5	7.5	10/32	1709	50
225/55R16	95V	BSW	25.8	9.1	6.0	7.0	8.0	10/32	1521	44
225/60R16	98H	BSW	26.7	9.0	6.0	6.5	8.0	10/32	1653	44
235/60R16	100H	BSW	27.1	9.4	6.5	7.0	8.5	10/32	1764	44
235/55R17	103V XL	BSW	27.2	9.6	6.5	7.5	8.5	10/32	1929	50

PRAGMATRA | MP10

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
175/70R13	82H	BSW	22.7	6.9	4.5	5.0	6.0	10/32	1047	44
175/65R14	82H	BSW	23.0	6.9	5.0	5.0	6.0	10/32	1047	44
175/70R14	84H	BSW	23.7	6.9	4.5	5.0	6.0	10/32	1102	44
185/60R14	82H	BSW	22.8	7.3	5.0	5.5	6.5	10/32	1047	44
185/65R14	86H	BSW	23.5	7.3	5.0	5.5	6.5	10/32	1168	44
185/70R14	88H	BSW	24.3	7.3	4.5	5.5	6.0	10/32	1235	44
185/55R15	82H	BSW	23.0	7.3	5.0	6.0	6.5	10/32	1047	44
185/60R15	84H	BSW	23.7	7.3	5.0	5.5	6.5	10/32	1102	44
185/65R15	88H	BSW	24.4	7.3	5.0	5.5	6.5	10/32	1235	44
195/55R15	85H	BSW	23.4	7.7	5.5	6.0	7.0	10/32	1135	44
195/60R15	88H	BSW	24.2	7.7	5.5	6.0	7.0	10/32	1235	44
195/65R15	91H	BSW	25.0	7.7	5.5	6.0	7.0	10/32	1356	44
205/55R16	91V	BSW	24.9	8.1	5.5	6.5	7.5	10/32	1356	44
215/55R16	93V	BSW	25.3	8.5	6.0	7.0	7.5	10/32	1433	44

S-PRO

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
215/65R16	98H	BSW	27.1	8.7	6.0	6.5	7.5	11/32	1653	44
245/70R16	107T	BSW	29.5	9.6	6.5	7.0	8.0	11/32	2149	44
265/70R16	112T	BSW	30.6	10.6	7.0	8.0	9.0	11/32	2469	44
225/60R17	99H	BSW	27.6	9.0	6.0	6.5	8.0	11/32	1709	44
225/65R17	102H	BSW	28.7	9.0	6.0	6.5	8.0	11/32	1874	44
235/55R17	103V XL	BSW	27.2	9.7	6.5	7.5	8.5	11/32	1929	50
235/65R17	104V	BSW	29.2	9.4	6.5	7.0	8.5	11/32	1984	44
265/65R17	112H	BSW	30.7	10.7	7.5	8.0	9.5	11/32	2469	44
225/60R18	100V	BSW	28.6	8.9	6.0	6.5	8.0	11/32	1764	44



S-PRO CONTINUED



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
235/50R18	101W XL	BSW	27.4	9.6	6.5	7.5	8.5	11/32	1819	50
235/55R18	100W	BSW	28.2	9.7	6.5	7.5	8.5	11/32	1764	51
235/60R18	107V XL	BSW	29.2	9.4	6.5	7.0	8.5	11/32	2149	50
255/55R18	109W XL	BSW	29.2	10.3	7.0	8.0	9.0	11/32	2271	50
265/60R18	114V XL	BSW	30.5	10.7	7.5	8.0	9.5	11/32	2601	50
225/55R19	99W	BSW	28.9	9.2	6.0	7.0	8.0	11/32	1709	51
235/45R19	99W XL	BSW	27.4	9.4	7.5	8.0	9.0	11/32	1709	50
235/50R19	99W	BSW	28.5	9.7	6.5	7.5	8.5	11/32	1709	51
235/55R19	101V	BSW	29.3	9.6	6.5	7.5	8.5	11/32	1819	44
255/45R19	104W XL	BSW	28.2	10.2	8.0	8.5	9.5	11/32	1984	50
255/50R19	107W XL	BSW	29.3	10.4	7.0	8.0	9.0	11/32	2149	50
245/50R20	102W	BSW	29.9	10.0	7.0	7.5	8.5	11/32	1874	51
265/50R20	112W XL	BSW	30.8	10.8	7.5	8.5	9.5	11/32	2469	50
265/55R20	113V XL	BSW	31.5	11.0	TBD	8.5	TBD	11/32	2535	50
275/40R20	106W XL	BSW	28.9	10.8	9.0	9.5	11.0	10/32	2094	50
275/45R20	110W XL	BSW	29.8	10.8	8.5	9.0	10.5	11/32	2337	50
275/55R20	117W XL	BSW	31.9	11.3	7.5	8.5	9.5	11/32	2833	50
285/50R20	112V	BSW	31.4	11.7	8.0	9.0	10.0	11/32	2469	44
265/40R20	106V XL	BSW	30.6	10.6	9.0	9.5	10.5	11/32	2094	50
265/45R22	109V XL	BSW	31.5	10.5	TBD	9.0	TBD	11/32	2271	50

MARAUDER | S2



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
205/70R15	96H	BSW	26.4	8.2	5.0	6.0	7.0	11/32	1565	36
225/70R15	100H	BSW	27.4	8.9	6.0	6.5	7.5	12/32	1764	36
225/75R15	102H	BSW	28.3	9.0	6.0	6.0	7.5	11/32	1874	36
235/70R15	103H	BSW	28.0	9.4	6.0	7.0	8.0	12/32	1929	36
215/65R16	102H XL	BSW	27.0	8.7	6.0	6.5	7.5	10/32	1874	50
215/70R16	100H	BSW	27.9	8.7	5.5	6.5	7.0	11/32	1764	36
225/70R16	107H XL	BSW	28.4	9.0	6.0	6.5	7.5	12/32	2149	42
235/60R16	104H XL	BSW	27.2	9.4	6.5	7.0	8.5	10/32	1984	50
245/70R16	111H XL	BSW	29.5	9.8	6.5	7.0	8.0	12/32	2403	42
255/65R16	109H	BSW	29.2	10.2	7.0	7.5	9.0	10/32	2270	44
265/70R16	112H	BSW	30.7	10.6	7.0	8.0	9.0	12/32	2469	36
235/65R17	104V	BSW	29.1	9.2	6.5	7.0	8.5	10/32	1984	44
255/60R17	110H XL	BSW	29.1	10.1	7.0	7.5	9.0	11/32	2337	50

MARAUDER | S2 CONTINUED

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
255/65R17	110H	BSW	30.1	10.1	7.0	7.5	9.0	10/32	2337	44
265/65R17	112H	BSW	30.6	10.6	7.5	8.0	9.5	10/32	2469	44
275/55R17	109V	BSW	29.0	10.9	7.5	8.5	9.5	11/32	2271	44
235/55R18	104V XL	BSW	28.3	9.5	6.5	7.5	8.5	11/32	1984	50
235/55R18	100V	BSW	28.3	9.5	6.5	7.5	8.5	11/32	1764	44
235/60R18	107V XL	BSW	29.2	9.3	6.5	7.0	8.5	10/32	2149	50
255/55R18	109V XL	BSW	29.1	10.2	7.0	8.0	9.0	11/32	2271	50
265/60R18	110H	BSW	30.6	10.7	7.5	8.0	9.5	11/32	2337	44
255/50R19	107V XL	BSW	29.1	10.3	7.0	8.0	9.0	11/32	2150	50
285/45R19	111V XL	BSW	28.9	11.3	9.0	9.5	10.5	11/32	2403	50
245/40R20	99W XL	BSW	27.6	9.7	8.0	8.5	9.5	11/32	1709	50
245/45R20	99W	BSW	28.5	9.6	7.5	8.0	9.0	11/32	1709	44
255/45R20	105V XL	BSW	29.1	10.0	8.0	8.5	9.5	11/32	2039	50
265/50R20	112V XL	BSW	30.5	10.7	7.5	8.5	9.5	12/32	2469	50
275/40R20	106V XL	BSW	28.7	10.9	9.0	9.5	11.0	11/32	2094	50
275/45R20	111V XL	BSW	29.7	10.6	8.5	9.0	10.5	11/32	2403	50
275/55R20	117V XL	BSW	32.0	10.9	7.5	8.5	9.5	11/32	2833	50
285/50R20	112V	BSW	31.3	11.5	8.0	9.0	10.0	12/32	2469	44
295/40R20	110V XL	BSW	29.1	11.8	10.0	10.5	11.5	12/32	2337	50
295/45R20	114V XL	BSW	30.4	11.7	9.5	10.0	11.0	11/32	2601	50
305/50R20	116V	BSW	32.0	12.4	8.5	9.5	11.0	12/32	2756	44
265/40R22	106V XL	BSW	30.4	10.8	9.0	9.5	10.5	11/32	2094	50
305/40R22	114V XL	BSW	31.6	12.2	10.0	11.0	12.0	10/32	2601	50
305/45R22	118V XL	BSW	32.8	11.9	9.5	10.0	11.5	12/32	2910	50
295/35R24	110V XL	BSW	TBD	TBD	10.0	10.5	11.5	TBD	2337	50
305/35R24	114V XL	BSW	32.6	12.3	10.0	11.0	12.0	TBD	2061	50
305/30R26	111V XL	BSW	TBD	TBD	10.5	11.0	11.5	TBD	TBD	50



ESCAPADE | CUV

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
215/65R16	95H	BSW	27.2	8.5	6.0	6.5	7.5	10/32	1653	44
225/60R17	99V	BSW	27.8	8.7	6.0	6.5	8.0	10/32	1709	44
225/65R17	102V	BSW	28.5	8.6	6.0	6.5	8.0	10/32	1874	44
235/55R17	103V XL	BSW	27.3	9.5	6.5	7.5	8.5	11/32	1929	50
235/60R17	102V	BSW	28.1	9.4	6.5	7.0	8.5	10/32	1874	44
235/65R17	104V	BSW	29.1	9.4	6.5	7.0	8.5	10/32	1984	44



ESCAPADE | CUV CONTINUED



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
245/65R17	107V	BSW	29.6	9.7	7.0	7.0	8.5	10/32	2149	44
255/60R17	106V	BSW	29.2	9.8	7.0	7.5	9.0	11/32	2094	44
275/55R17	109V	BSW	29.0	10.9	7.5	8.5	9.5	11/32	2271	44
235/50R18	101V XL	BSW	27.4	9.6	6.5	7.5	8.5	10/32	1819	50
235/55R18	100V	BSW	28.3	9.3	6.5	7.5	8.5	11/32	1764	44
235/60R18	103V	BSW	29.1	9.2	6.5	7.0	8.5	11/32	1929	44
235/65R18	106V	BSW	30.2	9.4	6.5	7.0	8.5	10/32	2094	44
245/60R18	105V	BSW	29.6	9.6	7.0	7.0	8.5	11/32	2039	44
255/55R18	109V XL	BSW	29.1	10.2	7.0	8.0	9.0	11/32	2271	50
255/65R18	111V	BSW	31.1	10.2	7.0	7.5	9.0	10/32	2403	44
265/60R18	114V XL	BSW	30.6	10.5	7.5	8.0	9.5	10/32	2601	50
235/55R19	105V XL	BSW	29.3	9.5	6.5	7.5	8.5	10/32	2039	50
245/55R19	103V	BSW	29.4	9.8	7.0	7.5	8.5	10/32	1929	44
255/50R19	107V XL	BSW	29.1	10.5	7.0	8.0	9.0	10/32	2149	50
255/55R19	111V XL	BSW	30.2	10.2	7.0	8.0	9.0	11/32	2403	44
255/60R19	109V	BSW	31.1	10.2	7.0	7.5	9.0	10/32	2271	44
245/50R20	102V	BSW	29.7	10.0	7.0	7.5	8.5	11/32	1874	44

BRAVO | HP-M3



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
165/65R13	77H	BSW	21.4	6.9	4.5	5.0	6.0	10/32	908	44
175/60R13	77H	BSW	21.3	7.0	5.0	5.0	6.0	10/32	908	44
185/65R14	86H	BSW	23.2	7.8	5.0	5.5	6.5	10/32	1168	44
205/60R14	88H	BSW	23.5	8.8	5.5	6.0	7.5	10/32	1235	44
185/65R15	88H	BSW	24.2	7.8	5.0	5.5	6.5	10/32	1235	44
205/60R15	91H	BSW	24.5	8.8	5.5	6.0	7.5	10/32	1356	44
205/70R15	96H	BSW	26.4	8.3	5.0	6.0	7.0	10/32	1565	44
215/70R15	98H	BSW	27.0	8.8	5.5	6.5	7.0	10/32	1653	44
225/60R15	96H	BSW	25.6	9.1	6.0	6.5	8.0	10/32	1565	44
255/70R15	108H	BSW	29.1	10.3	6.5	7.5	8.5	11/32	2205	44
265/70R15	112H	BSW	29.6	10.9	7.0	8.0	9.0	10/32	2469	44
195/55R16	87V	BSW	24.4	7.7	5.5	6.0	7.0	10/32	1201	44
205/50R16	87V	BSW	TBD	TBD	5.5	6.5	7.5	TBD	TBD	TBD
205/55R16	91V	BSW	24.9	8.3	5.5	6.5	7.5	10/32	1356	44
205/60R16	92V	BSW	25.7	8.2	5.5	6.0	7.5	10/32	1389	44
205/65R16	95H	BSW	26.7	8.3	5.5	6.0	7.5	10/32	1521	44
205/70R16	97H	BSW	27.4	8.1	5.0	6.0	7.0	10/32	1609	44

BRAVO | HP-M3 CONTINUED

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
215/55R16	93V	BSW	25.0	9.2	6.0	7.0	7.5	10/32	1433	44
215/60R16	95V	BSW	25.9	8.8	6.0	6.5	7.5	10/32	1521	44
215/65R16	98V	BSW	26.9	8.5	6.0	6.5	7.5	11/32	1653	44
215/65R16	102H XL	BSW	26.9	8.7	6.0	6.5	7.5	10/32	1874	50
215/70R16	100H	BSW	28.0	8.5	5.5	6.5	7.0	11/32	1764	44
215/70R16	104H XL	BSW	28.0	8.7	5.5	6.5	7.0	10/32	1984	50
225/50R16	92V	BSW	24.9	9.1	6.0	7.0	8.0	10/32	1389	44
225/55R16	95V	BSW	25.6	9.1	6.0	7.0	8.0	10/32	1521	44
225/60R16	98V	BSW	26.7	9.1	6.0	6.5	8.0	10/32	1653	44
225/65R16	100V	BSW	27.6	9.2	6.0	6.5	8.0	10/32	1764	44
225/70R16	107H XL	BSW	28.5	9.0	6.0	6.5	7.5	10/32	2149	50
225/75R16	104V	BSW	29.3	8.9	6.0	6.0	7.5	10/32	1984	44
235/60R16	100V	BSW	27.1	9.5	6.5	7.0	8.5	10/32	1764	44
235/65R16	103V	BSW	28.0	9.7	6.5	7.0	8.5	10/32	1929	44
235/70R16	109H XL	BSW	29.0	9.5	6.0	7.0	8.0	10/32	2271	50
245/70R16	107H	BSW	29.6	9.8	6.5	7.0	8.0	10/32	2149	44
265/70R16	112H	BSW	30.6	10.4	7.0	8.0	9.0	11/32	2469	44
205/45R17	88V XL	BSW	24.3	8.0	6.5	7.0	7.5	10/32	1235	50
205/50R17	93V XL	BSW	25.3	8.3	5.5	6.5	7.5	10/32	1433	50
215/45R17	91V XL	BSW	24.6	8.4	7.0	7.0	8.0	10/32	1356	50
215/50R17	95V XL	BSW	25.5	8.9	6.0	7.0	7.5	11/32	1521	50
215/55R17	94V	BSW	26.3	8.9	6.0	7.0	7.5	10/32	1477	44
215/60R17	96H	BSW	27.2	8.5	6.0	6.5	7.5	11/32	1565	44
215/60R17	100V XL	BSW	27.2	8.7	6.0	6.5	7.5	10/32	1764	50
215/65R17	99V	BSW	27.9	8.6	6.0	6.5	7.5	10/32	1709	44
215/70R17	101H	BSW	28.9	8.7	5.5	6.5	7.0	10/32	1819	44
225/45R17	91V	BSW	24.9	8.8	7.0	7.5	8.5	10/32	1356	44
225/50R17	94V	BSW	26.0	9.1	6.0	7.0	8.0	10/32	1477	44
225/55R17	97V	BSW	27.4	9.4	6.0	7.0	8.0	10/32	1609	44
225/60R17	99H	BSW	27.6	8.9	6.0	6.5	8.0	11/32	1709	44
225/65R17	102V	BSW	28.5	8.9	6.0	6.5	8.0	11/32	1874	44
225/65R17	106V XL	BSW	28.6	9.1	6.0	6.5	8.0	10/32	2094	50
235/45ZR17	94W	BSW	25.3	9.3	7.5	8.0	9.0	10/32	1477	51
235/50R17	100V XL	BSW	26.3	9.3	6.5	7.5	8.5	10/32	1764	50
235/55R17	99V	BSW	27.2	9.3	6.5	7.5	8.5	11/32	1709	44
235/55R17	103V XL	BSW	27.1	9.5	6.5	7.5	8.5	10/32	1929	50
235/60R17	106V XL	BSW	28.2	9.5	6.5	7.0	8.5	10/32	2094	50
235/65R17	104H	BSW	29.0	9.3	6.5	7.0	8.5	11/32	1984	44
235/65R17	108V XL	BSW	29.0	9.5	6.5	7.0	8.5	10/32	2205	50
245/40R17	95V XL	BSW	24.8	9.8	8.0	8.5	9.5	10/32	1521	50



BRAVO | HP-M3 CONTINUED



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
245/45R17	99V XL	BSW	25.6	9.6	7.5	8.0	9.0	10/32	1709	50
245/65R17	107H	BSW	29.5	9.6	7.0	7.0	8.5	11/32	2149	44
245/65R17	111V XL	BSW	29.7	9.9	7.0	7.0	8.5	10/32	2403	50
245/70R17	114H XL	BSW	30.5	9.8	6.5	7.0	8.0	10/32	2601	50
255/40R17	98V XL	BSW	25.1	10.2	8.5	9.0	10.0	10/32	1653	50
255/60R17	106V	BSW	29.0	10.0	7.0	7.5	9.0	11/32	2094	44
265/65R17	112H	BSW	30.7	10.4	7.5	8.0	9.5	11/32	2469	44
275/55R17	109V	BSW	28.9	10.8	7.5	8.5	9.5	11/32	2271	44
215/45R18	93W XL	BSW	25.3	9.1	7.0	7.0	8.0	10/32	1433	50
215/55R18	95H	BSW	27.3	8.5	6.0	7.0	7.5	11/32	1521	44
215/55R18	99V XL	BSW	27.3	8.7	6.0	7.0	7.5	10/32	1709	50
225/40R18	92W XL	BSW	24.8	9.9	7.5	8.0	9.0	10/32	1389	50
225/45R18	95W	BSW	25.9	8.9	7.0	7.5	8.5	10/32	1521	50
225/50R18	99W XL	BSW	27.0	9.0	6.0	7.0	8.0	10/32	1709	50
225/55R18	98V	BSW	27.8	8.9	6.0	7.0	8.0	11/32	1653	44
225/60R18	100V	BSW	28.6	8.9	6.0	6.5	8.0	11/32	1764	44
225/60R18	100W	BSW	28.5	9.3	6.0	6.5	8.0	10/32	1764	51
235/40R18	95W XL	BSW	25.4	9.5	8.0	8.5	9.5	10/32	1521	50
235/45R18	94W	BSW	26.3	9.3	7.5	8.0	9.0	10/32	1477	51
235/50R18	97V	BSW	27.3	9.3	6.5	7.5	8.5	10/32	1609	44
235/50R18	101W XL	BSW	27.4	9.4	6.5	7.5	8.5	10/32	1819	50
235/55R18	100V	BSW	28.1	9.5	6.5	7.5	8.5	10/32	1764	44
235/60R18	103V	BSW	29.1	9.3	6.5	7.0	8.5	11/32	1929	44
235/60R18	107V XL	BSW	29.2	9.5	6.5	7.0	8.5	10/32	2149	50
235/65R18	106V	BSW	30.2	9.3	6.5	7.0	8.5	11/32	2094	44
235/65R18	110V XL	BSW	30.2	9.5	6.5	7.0	8.5	10/32	2337	50
245/40R18	97W XL	BSW	25.7	9.8	8.0	8.5	9.5	10/32	1609	50
245/45R18	96V	BSW	26.7	9.6	7.5	8.0	9.0	10/32	1565	44
245/45R18	100V XL	BSW	26.8	9.3	7.5	8.0	9.0	10/32	1764	50
245/55R18	103W	BSW	28.6	9.8	7.0	7.5	8.5	10/32	1929	51
245/60R18	105V	BSW	29.6	9.6	7.0	7.0	8.5	11/32	2039	44
255/35R18	94W XL	BSW	TBD	TBD	8.5	9.0	10.0	TBD	TBD	TBD
255/40R18	99W XL	BSW	26.0	10.2	8.5	9.0	10.0	10/32	1709	50
255/45R18	103W XL	BSW	27.1	10.1	8.0	8.5	9.5	10/32	1929	50
255/55R18	109V XL	BSW	29.0	10.0	7.0	8.0	9.0	11/32	2271	50
255/60R18	112V XL	BSW	30.1	10.0	7.0	7.5	9.0	11/32	2469	50
255/65R18	115V XL	BSW	31.0	10.4	7.0	7.5	9.0	10/32	2679	50
255/70R18	113H	BSW	32.1	10.2	6.5	7.5	8.5	10/32	2535	44
265/60R18	114V XL	BSW	30.5	10.8	7.5	8.0	9.5	10/32	2601	50
265/65R18	114H	BSW	31.7	11.0	7.5	8.0	9.5	10/32	2601	44

XL - Extra Load; BSW - Black Sidewall; TBD - To Be Determined

BRAVO | HP-M3 CONTINUED

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
265/70R18	116H	BSW	32.6	10.7	7.0	8.0	9.0	10/32	2756	44
225/40R19	93W XL	BSW	26.2	9.1	7.5	8.0	9.0	10/32	1433	50
225/45R19	96W XL	BSW	27.0	8.9	7.0	7.5	8.5	10/32	1565	50
225/55R19	99V	BSW	28.8	9.2	6.0	7.0	8.0	10/32	1709	44
235/40R19	96W XL	BSW	26.5	9.7	8.0	8.5	9.5	10/32	1565	50
235/50R19	99V	BSW	28.3	9.6	6.5	7.5	8.5	10/32	1709	44
235/50R19	103W XL	BSW	28.3	9.6	6.5	7.5	8.5	10/32	1929	50
235/55R19	105V XL	BSW	29.2	9.3	6.5	7.5	8.5	11/32	2039	50
235/55R19	101V	BSW	29.2	9.5	6.5	7.5	8.5	10/32	1819	44
245/40R19	98W XL	BSW	26.7	9.7	8.0	8.5	9.5	10/32	1653	50
245/45R19	98W	BSW	27.6	9.6	7.5	8.0	9.0	10/32	1653	51
245/55R19	103V	BSW	29.6	9.6	7.0	7.5	8.5	11/32	1929	44
255/40R19	100W XL	BSW	27.1	10.2	8.5	9.0	10.0	10/32	1764	50
255/45R19	104W XL	BSW	28.1	10.1	8.0	8.5	9.5	10/32	1984	50
255/50R19	103V	BSW	29.3	10.0	7.0	8.0	9.0	10/32	1929	44
255/50R19	107V XL	BSW	29.1	10.4	7.0	8.0	9.0	10/32	2149	50
255/55R19	111V XL	BSW	30.0	10.0	7.0	8.0	9.0	11/32	2403	50
255/55R19	111W XL	BSW	30.0	10.4	7.0	8.0	9.0	10/32	2403	50
255/60R19	109H	BSW	31.1	10.0	7.0	7.5	9.0	11/32	2271	44
255/60R19	113V XL	BSW	31.1	10.3	7.0	7.5	9.0	10/32	2535	50
265/50R19	110V XL	BSW	29.5	10.4	7.5	8.5	9.5	10/32	2337	50
275/40R19	105W XL	BSW	27.8	10.8	9.0	9.5	11.0	10/32	2039	50
285/45R19	107V	BSW	29.0	11.2	9.0	9.5	10.5	10/32	2150	44
235/55R20	102V	BSW	30.2	9.3	6.5	7.5	8.5	11/32	1874	44
235/55R20	105V XL	BSW	30.2	9.5	6.5	7.5	8.5	10/32	2039	50
245/40R20	99W XL	BSW	27.9	9.8	8.0	8.5	9.5	10/32	1709	50
245/45R20	99W	BSW	28.7	9.5	7.5	8.0	9.0	10/32	1709	51
245/50R20	102V	BSW	29.8	9.7	7.0	7.5	8.5	10/32	1874	44
255/45R20	105V XL	BSW	29.1	10.0	8.0	8.5	9.5	10/32	2039	50
255/45ZR20	105W XL	BSW	28.9	10.2	8.0	8.5	9.5	9/32	2039	50
255/50R20	109V XL	BSW	30.1	10.0	7.0	8.0	9.0	10/32	2271	50
255/55R20	110V XL	BSW	31.1	10.4	7.0	8.0	9.0	10/32	2337	50
265/50R20	107V	BSW	30.5	10.4	7.5	8.5	9.5	10/32	2149	44
265/50R20	111V XL	BSW	30.4	10.8	7.5	8.5	9.5	10/32	2403	50
275/40R20	106W XL	BSW	28.8	10.8	9.0	9.5	11.0	10/32	2094	50
275/45R20	110V XL	BSW	29.8	10.8	8.5	9.0	10.5	10/32	2337	50
275/45R20	110W XL	BSW	29.6	10.8	8.5	9.0	10.5	10/32	2337	50
285/50R20	116V XL	BSW	31.3	11.7	8.0	9.0	10.0	10/32	2756	50



PRAGMATRA | SUV MP15



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
205/65R15	94V	BSW	25.5	8.1	5.5	6.0	7.5	10/32	1477	44
205/70R15	96H	BSW	26.3	8.1	5.0	6.0	7.0	10/32	1565	44
215/70R15	98V	BSW	26.9	8.5	5.5	6.5	7.0	10/32	1653	44
205/65R16	95V	BSW	26.5	8.1	5.5	6.0	7.5	10/32	1521	44
205/70R16	97H	BSW	27.3	8.1	5.0	6.0	7.0	10/32	1609	44
215/65R16	98H	BSW	27.0	8.5	6.0	6.5	7.5	10/32	1653	44
215/70R16	100H	BSW	27.9	8.5	5.5	6.5	7.0	10/32	1764	44
235/70R16	106H	BSW	29.0	9.3	6.0	7.0	8.0	10/32	2094	44
215/60R17	96V	BSW	27.2	8.5	6.0	6.5	7.0	10/32	1565	44
225/60R17	99V	BSW	27.6	8.9	6.0	6.5	7.0	10/32	1709	44
225/65R17	102V	BSW	28.5	8.9	6.0	6.5	8.0	10/32	1874	44
235/55R17	99V	BSW	27.2	9.3	6.5	7.5	8.5	10/32	1709	44
235/65R17	104H	BSW	29.1	9.3	6.5	7.0	8.5	10/32	1984	44
215/55R18	95V	BSW	27.3	8.5	6.0	7.0	7.5	10/32	1521	44
225/55R18	98V	BSW	27.8	8.9	6.0	7.0	8.0	10/32	1653	44

BRAVO | HT-770



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
235/60R14	96H	OWL	25.2	9.3	6.5	7.0	8.5	13/32	1565	44
225/70R15	100T	BSW	27.6	9.0	6.0	6.5	7.5	13/32	1764	44
235/70R15	107S XL	OWL	28.0	9.3	6.0	7.0	8.0	13/32	2149	50
235/75R15	109S XL	OWL	28.9	9.3	6.0	6.5	8.0	13/32	2271	50
255/60R15	102T	OWL	27.1	10.0	7.0	7.5	9.0	13/32	1874	44
265/50R15	99H	BSW	25.5	10.4	7.5	8.5	9.5	13/32	1720	44
215/70R16	100T	OWL	28.0	8.5	5.5	6.5	7.0	13/32	1764	44
225/70R16	107T XL	OWL	28.5	8.9	6.0	6.5	7.5	13/32	2149	50
225/75R16	104T	BSW	29.3	8.4	6.0	6.0	7.5	12/32	1984	44
235/65R16	107T XL	OWL	28.0	9.3	6.5	7.0	8.5	13/32	2149	50
235/70R16	106T	OWL	29.0	9.3	6.0	7.0	8.0	13/32	2094	44
235/75R16	112S XL	OWL	29.9	9.3	6.0	6.5	8.0	13/32	2469	50
245/70R16	111S XL	OWL	29.4	9.6	6.5	7.0	8.0	13/32	2403	50
245/70R16	111T XL	BSW	29.4	9.7	6.5	7.0	8.0	13/32	2403	50
245/75R16	111S	OWL	30.5	9.6	6.5	7.0	8.0	13/32	2403	44
255/70R16	111S	OWL	30.1	10.0	6.5	7.5	8.5	13/32	2403	44
265/70R16	112S	OWL	30.7	10.4	7.0	8.0	9.0	14/32	2469	44
265/70R16	112T	BSW	30.7	10.6	7.0	8.0	9.0	13/32	2469	44
265/75R16	116T	OWL	31.6	10.4	7.0	7.5	9.0	14/32	2756	44

BRAVO | HT-770 CONTINUED

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
275/60R16	109T	OWL	29.1	10.8	7.5	8.0	9.5	13/32	2271	44
225/65R17	102H	OWL	28.6	8.9	6.0	6.5	8.0	13/32	1874	44
235/60R17	102H	OWL	28.2	9.3	6.5	7.0	8.5	13/32	1874	44
235/65R17	104H	OWL	29.1	9.3	6.5	7.0	8.5	13/32	1984	44
235/70R17	111S XL	OWL	30.0	9.3	6.0	7.0	8.0	13/32	2403	50
235/75R17	109S	OWL	31.0	9.3	6.0	6.5	8.0	13/32	2271	44
245/65R17	111H XL	BSW	29.6	9.6	7.0	7.0	8.5	13/32	2403	50
245/65R17	111H XL	OWL	29.4	9.6	7.0	7.0	8.5	13/32	2403	50
245/70R17	110S	OWL	30.6	9.6	6.5	7.0	8.0	13/32	2337	44
245/75R17	112T	BSW	31.5	9.4	6.5	7.0	8.0	TBD	2469	44
255/60R17	110T XL	OWL	29.1	10.0	7.0	7.5	9.0	13/32	2337	50
255/65R17	110S	OWL	30.2	10.0	7.0	7.5	9.0	13/32	2337	44
255/70R17	112S	OWL	31.1	10.0	6.5	7.5	8.5	13/32	2469	44
265/65R17	112S	OWL	30.5	10.4	7.5	8.0	9.5	13/32	2469	44
265/70R17	115T	OWL	31.5	10.6	7.0	8.0	9.0	14/32	2679	44
275/60R17	110S	OWL	30.0	10.8	7.5	8.0	9.5	13/32	2337	44
255/60R18	108H	BSW	30.1	10.2	7.0	7.5	9.0	11/32	2205	44
255/70R18	113S	BSW	32.0	9.9	TBD	TBD	TBD	13/32	2535	44
265/60R18	114H XL	OWL	30.6	10.4	7.5	8.0	9.5	13/32	2601	50
265/65R18	114H	BSW	31.5	10.7	7.5	8.0	9.5	13/32	2401	44
265/70R18	116H	BSW	32.5	10.3	7.0	8.0	9.0	13/32	2756	44
275/65R18	116T	OWL	32.2	10.8	7.5	8.0	9.5	13/32	2756	44
275/55R20	117H XL	OWL	32.0	10.8	7.5	8.5	9.5	13/32	2833	50
275/60R20	115T	OWL	32.9	10.8	7.5	8.0	9.5	13/32	2679	44
LT225/75R16	115/112S 10PR	OWL	29.3	8.9	6.0	6.0	7.0	14/32	S2680/D2470	80
LT235/85R16*	120/116S 10PR	OWL	31.8	9.3	6.0	6.5	7.5	16/32	S3042/D2778	80
LT265/75R16*	123/120S 10PR	OWL	31.6	10.4	7.0	7.5	8.0	16/32	S3415/D3085	80
LT225/75R17	116/113R 10PR	BSW	30.2	8.3	6.0	6.0	7.5	TBD	S2755/D2535	80
LT235/80R17*	120/117S 10PR	OWL	31.8	9.3	6.0	6.5	7.5	16/32	S3085/D2835	80
LT245/70R17*	119/116S 10PR	OWL	30.6	9.6	6.5	7.0	8.0	16/32	S3000/D2755	80
LT245/75R17*	121/118S 10PR	BSW	31.4	9.1	6.5	7.0	7.5	TBD	S3195/D2910	80
LT265/70R17*	121/118S 10PR	OWL	31.6	10.4	7.0	8.0	8.5	16/32	S3195/D2910	80
LT265/70R18*	124/121S 10PR	BSW	32.6	10.2	7.0	8.0	9.0	TBD	S3525/D3195	80
LT275/65R18*	123/120S 10PR	BSW	32.0	11.1	7.5	8.0	9.0	TBD	S3415/D3085	80
LT275/70R18	121/118S 8PR	OWL	31.8	9.2	7.0	8.0	8.5	14/32	S3195/D2910	65
LT275/70R18*	125/122S 10PR	OWL	33.2	10.8	7.0	8.0	8.5	16/32	S3640/D3305	80
LT265/60R20	121/118R 10PR	BSW	32.4	10.9	7.5	8.0	9.5	TBD	S3195/D2910	80
LT275/65R20	126/123R 10PR	BSW	34.0	11.1	7.5	8.0	9.5	TBD	S3750/D3415	80
30X9.50R15LT	104S	BSW	29.3	9.1	6.5	7.5	8.5	16/32	1985	50
31X10.50R15LT	109S	BSW	30.3	10.8	7.0	8.5	9.0	16/32	2270	50



*3-ply sidewall; XL - Extra Load; BSW - Black Sidewall; OWL - Outline White Lettering; TBD - To Be Determined

RAZR | AT



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
225/55R17	101H	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
225/65R17	106H	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT265/75R16	123/120R 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT285/75R16	126/123R 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT315/75R16	127/124R 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT265/70R17	121/118S 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT285/70R17	118S 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT295/70R17	121/118R 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT305/65R17	121/118R 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT305/70R17	121/118S 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT315/70R17	121/118S 8PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT265/70R18	124/121S 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT275/65R18	123/120S 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT275/70R18	125/122S 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT285/65R18	125/122S 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT285/75R18	129/126S 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT295/70R18	129/126S 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT305/60R18	121/118R 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT265/60R20	121/118S 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT275/65R20	126/123S 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT285/55R20	122/119S 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT285/65R20	127/124S 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT295/55R20	123/120S 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT295/60R20	126/123S 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT295/65R20	129/126S 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT305/55R20	121/118S 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT285/50R22	TBD	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT285/55R22	TBD	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LT325/50R22	122S 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
35X12.50R17LT	121R 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
37X12.50R17LT	124R 8PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
35X12.50R18LT	123Q 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
37X12.50R18LT	128R 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
35X12.50R20LT	121R 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
35X12.50R20LT	125Q 12PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
37X12.50R20LT	128R 12PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
37X13.50R20LT	127R 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
40X13.50R20LT	128Q 8PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
35X12.50R22LT	121Q 12PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
37X12.50R22LT	127Q 12PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
37X13.50R22LT	123Q 10PR	RBL	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD

BRAVO | AT-771

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
205/70R15	96T	OWL	26.3	8.1	5.0	6.0	7.0	13/32	1565	44
205/75R15	97T	OWL	27.1	8.1	5.0	5.5	7.0	13/32	1609	44
215/75R15	100S	OWL	27.8	8.5	5.5	6.0	7.0	13/32	1764	44
225/70R15	100S	OWL	27.4	8.9	6.0	6.5	7.5	13/32	1764	44
225/75R15	102S	OWL	28.3	8.9	6.0	6.0	7.5	13/32	1874	44
235/60R15	98S	OWL	26.2	9.3	6.5	7.0	8.5	13/32	1653	44
235/75R15	109S XL	OWL	28.9	9.3	6.0	6.5	8.0	13/32	2271	50
255/70R15	108T	OWL	29.1	10.0	6.5	7.5	8.5	13/32	2205	44
265/70R15	112S	OWL	29.6	10.4	7.0	8.0	9.0	13/32	2469	44
215/65R16	98T	OWL	27.0	8.5	6.0	6.5	7.5	13/32	1653	44
215/70R16	100T	OWL	28.0	8.7	5.5	6.5	7.0	13/32	1764	44
225/75R16	108S XL	OWL	29.3	8.9	6.0	6.0	7.5	13/32	2205	50
235/60R16	104H XL	BSW	27.1	9.3	6.5	7.0	8.5	13/32	1984	50
235/70R16	106T	OWL	29.0	9.3	6.0	7.0	8.0	13/32	2094	44
P235/70R16	106T	OWL	28.9	9.4	6.0	7.0	8.0	13/32	2094	44
245/70R16	107T	OWL	29.5	9.6	6.5	7.0	8.0	13/32	2149	44
245/75R16	111S	OWL	31.1	9.6	6.5	7.0	8.0	13/32	2403	44
255/65R16	109T	OWL	29.1	10.0	7.0	7.5	9.0	13/32	2271	44
255/70R16	111T	OWL	30.0	10.0	6.5	7.5	8.5	13/32	2403	44
265/70R16	112T	OWL	30.6	10.4	7.0	8.0	9.0	13/32	2469	44
265/75R16	116T	OWL	31.1	10.5	7.0	7.5	9.0	13/32	2756	44
275/70R16	114T	OWL	31.2	10.8	7.0	8.0	9.0	14/32	2601	44
225/60R17	103T XL	BSW	29.2	9.5	6.0	6.5	8.0	13/32	1929	50
225/65R17	102T	OWL	28.5	8.9	6.0	6.5	8.0	13/32	1874	44
235/65R17	104T	OWL	29.1	9.3	6.5	7.0	8.5	13/32	1984	44
235/75R17	109T	OWL	31.0	9.3	6.0	6.5	8.0	13/32	2271	44
245/65R17	107S	OWL	29.5	9.6	7.0	7.0	8.5	13/32	2149	44
245/65R17	111S XL	OWL	29.5	9.8	7.0	7.0	8.5	13/32	2403	50
245/70R17	110S	OWL	30.7	9.6	6.5	7.0	8.0	13/32	2337	44
255/65R17	110H	BSW	30.1	10.0	7.0	7.5	9.0	13/32	2337	44
255/70R17	112S	BSW	31.1	10.0	6.5	7.5	8.5	13/32	2469	44
265/65R17	112T	OWL	30.6	10.4	7.5	8.0	9.5	13/32	2469	44
265/70R17	115S	OWL	31.8	10.4	7.0	8.0	9.0	13/32	2679	44
275/65R17	115T	OWL	31.1	10.8	7.5	8.0	9.5	13/32	2679	44
285/65R17	116S	OWL	31.6	11.2	8.0	8.5	10.0	13/32	2756	44
255/55R18	109H XL	BSW	29.1	10.0	7.0	8.0	9.0	13/32	2271	50
255/60R18	112H XL	BSW	30.0	10.0	7.0	7.5	9.0	13/32	2469	50
265/60R18	114H XL	BSW	30.5	10.4	7.5	8.0	9.5	13/32	2601	50
265/60R18	110H	RWW	30.5	10.8	7.5	8.0	9.5	13/32	2337	44
265/65R18	114S	OWL	31.1	10.4	7.5	8.0	9.5	13/32	2601	44
265/70R18	116S	OWL	32.6	10.4	7.0	8.0	9.0	13/32	2756	44
275/65R18	116S	BSW	32.1	10.8	7.5	8.0	9.5	13/32	2756	44
285/60R18	116T	RWL	31.5	11.2	8.0	8.5	10.0	13/32	2756	44



BRAVO | AT-771 CONTINUED



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
265/50R20	111H XL	BSW	30.6	10.4	7.5	8.5	9.5	13/32	2403	50
275/55R20	117T XL	OWL	31.8	10.8	7.5	8.5	9.5	13/32	2833	50
275/60R20	115S	OWL	31.8	10.8	7.5	8.0	9.5	13/32	2679	44
305/50R20	120T XL	OWL	32.0	12.0	8.5	9.5	11.0	14/32	3086	50
LT235/75R15	104/101S 6PR	OWL	28.9	9.3	6.0	6.5	7.0	14/32	S1985/D1820	50
LT215/85R16*	115/112R 10PR	OWL	30.4	8.5	5.5	6.0	7.0	15/32	S2680/D2470	80
LT225/70R16	102/99S 6PR	OWL	28.4	8.9	6.0	6.5	7.0	16/32	S1875/D1710	50
LT225/75R16	115/112Q 10PR	OWL	29.3	8.9	6.0	6.0	7.0	14/32	S2680/D2470	80
LT235/70R16	104/101S 6PR	OWL	29.0	9.3	6.0	7.0	7.5	16/32	S1985/D1820	50
LT235/85R16*	120/116S 10PR	OWL	31.8	9.3	6.0	6.5	7.5	16/32	S3085/D2755	80
LT245/75R16	108/104S 6PR	OWL	30.5	9.6	6.5	7.0	8.0	16/32	S2205/D2006	50
LT245/75R16*	120/116Q 10PR	OWL	30.4	9.6	6.5	7.0	8.0	16/32	S3042/D2778	80
LT265/70R16	117/114S 8PR	OWL	30.6	10.4	7.0	8.0	8.5	16/32	S2835/D2600	65
LT265/75R16	119/116Q 8PR	OWL	31.7	10.4	7.0	7.5	8.0	16/32	S3000/D2755	65
LT265/75R16*	123/120Q 10PR	OWL	31.6	10.4	7.0	7.5	8.0	16/32	S3415/D3085	80
LT275/70R16	119/116S 8PR	OWL	31.1	10.8	7.0	8.0	8.5	17/32	S3000/D2755	65
LT285/75R16	122/119R 8PR	OWL	32.8	11.2	7.5	8.0	9.0	17/32	S3305/D3000	65
LT285/75R16*	126/123Q 10PR	OWL	32.8	11.2	7.5	8.0	9.0	17/32	S3750/D3415	80
LT305/70R16*	124/121R 10PR	OWL	32.8	12.3	8.0	9.0	9.5	17/32	S3525/D3195	65
LT315/75R16	121/118R 8PR	OWL	34.6	12.6	8.0	8.5	11.0	17/32	S3195/D2910	50
LT225/75R17*	116/113Q 10PR	OWL	30.4	8.9	6.0	6.0	7.5	14/32	S2755/D2535	80
LT235/80R17*	120/117R 10PR	OWL	31.8	9.3	6.0	6.5	7.5	16/32	S3085/D2835	80
LT245/70R17*	119/116R 10PR	OWL	30.5	9.7	6.5	7.0	8.0	15/32	S3000/D2755	80
LT245/75R17*	121/118S 10PR	OWL	31.5	9.6	6.5	7.0	7.5	16/32	S3195/D2910	80
LT255/75R17	111/108Q 6PR	OWL	TBD	TBD	6.5	7.0	8.5	16/32	S2405/D2205	50
LT265/65R17*	120/117S 10PR	OWL	30.6	10.4	7.5	8.0	9.5	16/32	S3085/D2835	80
LT265/70R17*	121/118R 10PR	OWL	31.6	10.4	7.0	8.0	8.5	16/32	S3195/D2910	80
LT275/65R17*	121/118S 10PR	BSW	31.1	11.0	7.5	8.0	9.5	16/32	S3195/D2910	80
LT285/70R17	121/118R 8PR	OWL	32.7	11.2	7.5	8.5	9.0	17/32	S3195/D2910	65
LT305/70R17	119/116Q 8PR	OWL	33.8	12.0	8.0	9.0	9.5	17/32	S3000/D2755	50
LT315/70R17	121/118R 8PR	OWL	34.4	12.4	8.0	9.5	11.0	17/32	S3195/D2910	50
LT265/70R18	124/121Q 10PR	OWL	32.7	10.7	7.0	8.0	9.0	16/32	S3525/D3195	80
LT275/65R18*	123/120S 10PR	OWL	32.1	10.8	7.5	8.0	9.0	16/32	S3415/D3085	80
LT275/70R18	125/122R 10PR	OWL	TBD	TBD	7.0	8.0	8.5	17/32	S3640/D3305	80
LT285/65R18*	125/122R 10PR	OWL	32.5	11.2	8.0	8.5	10.0	17/32	S3640/D3305	80
LT325/60R18	124/121Q 10PR	OWL	33.2	13.1	8.5	9.5	10.0	15/32	S3525/D3195	65
LT325/65R18*	121/118S 8PR	OWL	34.5	12.8	9.0	9.5	12.0	17/32	S3195/D2910	50
LT275/65R20	126/123R 10PR	BSW	34.1	11.0	7.5	8.0	9.5	16/32	S3750/D3415	80
LT285/55R20*	122/119S 10PR	OWL	32.5	11.2	8.0	9.0	10.0	16/32	S3305/D3000	80
LT305/55R20*	121/118S 10PR	BSW	33.3	12.0	8.5	9.5	11.0	16/32	S3195/D2910	65
LT325/60R20*	126/123S 10PR	OWL	35.3	12.8	9.0	9.5	12.0	16/32	S3750/D3415	65
27X8.50R14LT	95S 6PR	OWL	26.6	8.5	6.0	7.0	7.5	15/32	1520	50
30X9.50R15LT	104S 6PR	OWL	29.6	9.5	6.5	7.5	8.5	16/32	1985	50

*3-ply sidewall; XL - Extra Load; BSW - Black Sidewall; OWL - Outline White Lettering

BRAVO | AT-771 CONTINUED

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
31X10.50R15LT	109S 6PR	OWL	30.4	10.5	7.0	8.5	9.0	16/32	2270	50
33X12.50R15LT	108S 6PR	OWL	32.6	12.5	8.5	10.0	11.0	17/32	2205	35
35X12.50R15LT*	113Q 6PR	OWL	34.6	12.5	8.5	10.0	11.0	17/32	2535	35

BRAVO | AT-980

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
215/75R15	102S XL	OWL	27.7	8.1	5.5	6.0	7.0	14/32	1874	50
235/75R15	109S XL	OWL	28.9	9.3	6.0	6.5	8.0	13/32	2271	50
235/70R16	106T	OWL	29.1	9.2	6.0	7.0	8.0	14/32	2094	44
255/65R17	110S	OWL	30.1	10.2	7.0	7.5	9.0	13/32	2337	44
265/65R17	112T	OWL	30.6	10.5	7.5	8.0	9.5	17/32	2467	44
275/65R18	116S	OWL	32.1	10.9	7.5	8.0	9.5	13/32	2756	44
265/55R20	113H XL	BSW	31.4	10.8	7.5	8.0	9.0	13/32	2535	50
LT225/75R16	115/112S 10PR	OWL	29.3	8.8	6.0	6.0	7.0	16/32	S2680/D2470	80
LT235/85R16*	120/116S 10PR	BSW	31.7	9.3	6.0	7.0	7.5	16/32	S3042/D2778	80
LT245/70R16*	113/110S 8PR	OWL	29.7	9.7	7.0	8.0	8.5	16/32	S2535/D2335	65
LT245/75R16*	120/116S 10PR	OWL	30.5	9.8	6.5	7.0	8.0	16/32	S3042/D2778	80
LT255/70R16	115/112S 8PR	OWL	30.3	10.1	6.5	7.5	8.0	16/32	S2680/D2470	65
LT265/70R16	117/114S 8PR	OWL	30.8	10.6	7.0	8.0	8.5	16/32	S2835/D2600	65
LT265/75R16*	123/120Q 10PR	OWL	31.7	10.5	7.0	7.5	8.0	16/32	S3415/D3085	80
LT275/70R16	119/116Q 8PR	OWL	31.3	10.8	7.0	8.0	8.5	16/32	S3000/D2755	65
LT285/75R16	122/119R 8PR	OWL	32.8	11.4	7.5	8.0	9.0	17/32	S3305/D3000	65
LT225/70R17	110/107S 8PR	OWL	29.6	9.0	6.0	6.5	7.5	16/32	S2335/D2150	65
LT245/70R17	119/116S 10PR	OWL	30.6	9.3	6.5	7.0	8.0	16/32	S3000/D2755	80
LT265/65R17	117/114S 8PR	OWL	30.6	10.7	7.5	8.0	9.5	15/32	S2835/D2600	65
LT265/70R17	118/115Q 8PR	OWL	31.7	10.7	7.0	8.0	8.5	16/32	S2910/D2680	65
LT275/65R17	118/115S 8PR	OWL	31.2	11.0	7.5	8.0	9.5	15/32	S2910/D2680	65
LT285/70R17	121/118Q 8PR	OWL	32.8	11.5	7.5	8.5	9.0	17/32	S3195/D2910	65
LT255/60R18	112/109S 8PR	OWL	30.1	10.4	TBD	7.5	TBD	13/32	S2470/D2270	65
LT265/60R18	114/110S 8PR	OWL	30.6	10.8	7.5	8.0	9.5	13/32	S2600/D2335	65
LT285/60R18	118/115S 8PR	OWL	31.5	11.8	8.0	8.5	10.0	14/32	S2910/D2680	65
LT255/55R19	115/112S 10PR	BSW	30.2	10.1	TBD	8.0	TBD	13/32	S2680/D2470	80
30X9.50R15LT	104S 6PR	OWL	29.4	9.5	6.5	7.5	8.5	17/32	1985	50
31X10.50R15LT	109S 6PR	OWL	30.4	10.5	7.0	8.5	9.0	17/32	2270	50
32X11.50R15LT	113R 6PR	OWL	31.5	11.4	8.0	9.0	10.0	17/32	2535	50
33X10.50R15LT	114Q 6PR	OWL	32.4	10.9	7.0	8.5	9.0	17/32	2600	50
33X12.50R15LT	108Q 6PR	OWL	32.4	12.6	8.5	10.0	11.0	17/32	2205	35
35X12.50R15LT*	113Q 6PR	OWL	34.5	12.5	8.5	10.0	11.0	17/32	2535	35



*3-ply sidewall; XL - Extra Load; BSW - Black Sidewall; OWL - Outline White Lettering; TBD - To Be Determined



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
LT245/75R16*	120/116Q 10PR	RBL	30.4	10.2	6.5	7.0	8.0	18/32	S3042/D2778	80
LT265/75R16*	123/120Q 10PR	RBL	31.9	11.0	7.0	7.5	8.0	18/32	S3415/D3085	80
LT285/75R16*	126/123Q 10PR	RBL	33.0	11.8	7.5	8.0	9.0	18/32	S3750/D3415	80
LT315/75R16*	127/124Q 10PR	RBL	34.8	12.8	8.0	8.5	11.0	19/32	S3860/D3525	65
LT265/70R17*	121/118Q 10PR	RBL	31.9	11.1	7.0	8.0	8.5	18/32	S3195/D2910	80
LT285/70R17*	121/118Q 10PR	RBL	33.0	11.9	7.5	8.5	9.0	18/32	S3195/D2910	80
LT295/70R17*	121/118Q 10PR	RBL	33.5	12.2	7.5	8.5	10.0	19/32	S3195/D2910	80
LT305/70R17*	121/118Q 10PR	RBL	34.0	12.8	8.0	9.0	9.5	19/32	S3195/D2910	65
LT315/70R17*	121/118Q 8PR	RBL	34.6	13.3	8.0	9.5	11.0	19/32	S3195/D2910	50
LT275/65R18*	123/120Q 10PR	RBL	32.5	11.1	7.5	8.0	9.0	18/32	S3415/D3085	80
LT275/70R18*	125/122Q 10PR	RBL	33.5	11.3	7.0	8.0	8.5	18/32	S3640/D3305	80
LT285/65R18*	125/122Q 10PR	RBL	32.8	11.5	8.0	8.5	10.0	19/32	S3640/D3305	80
LT285/75R18*	129/126Q 10PR	RBL	35.0	11.8	7.5	8.0	9.5	18/32	S4080/D3750	80
LT295/65R18*	127/124Q 10PR	RBL	33.5	12.1	8.0	8.5	10.0	19/32	S3860/D3525	80
LT295/70R18*	129/126Q 10PR	RBL	34.6	12.3	7.5	8.5	10.0	19/32	S4080/D3750	80
LT275/65R20*	126/123Q 10PR	RBL	34.5	11.2	7.5	8.0	9.5	18/32	S3750/D3415	80
LT295/55R20*	123/120Q 10PR	RBL	33.4	12.1	8.0	9.5	10.0	19/32	S3415/D3085	80
LT295/60R20*	126/123Q 10PR	RBL	34.4	12.2	8.0	8.5	10.0	19/32	S3750/D3415	80
LT295/65R20*	129/126Q 10PR	RBL	35.7	12.0	8.0	8.5	10.0	19/32	S4080/D3750	80
32X11.50R15LT*	113Q 6PR	RBL	31.8	11.9	8.0	9.0	10.0	20/32	2535	50
33X10.50R15LT*	114Q 6PR	RBL	32.8	11.1	7.0	8.5	9.0	19/32	2600	50
33X12.50R15LT*	108Q 6PR	RBL	32.8	13.4	8.5	10.0	11.0	20/32	2205	35
35X12.50R15LT*	113Q 6PR	RBL	34.9	13.5	8.5	10.0	11.0	20/32	2535	35
35X12.50R17LT*	121Q 10PR	RBL	34.8	13.2	8.5	10.0	11.0	20/32	3195	65
35X13.50R17LT*	121Q 10PR	RBL	34.8	14.2	8.5	11.0	11.0	20/32	3195	65
37X12.50R17LT*	124Q 10PR	RBL	36.8	13.1	8.5	10.0	11.0	20/32	3525	65
37X13.50R17LT*	121Q 8PR	RBL	36.8	13.6	8.5	11.0	11.0	20/32	3195	50
40X13.50R17LT*	121Q 6PR	RBL	39.9	14.3	8.5	11.0	11.0	20/32	3195	35
35X12.50R18LT*	123Q 10PR	RBL	34.8	13.2	8.5	10.0	11.0	20/32	3415	65
35X12.50R18LT*	128Q 12PR	RBL	34.8	12.9	8.5	10.0	11.0	20/32	3970	80
37X12.50R18LT*	123Q 8PR	RBL	36.9	13.0	8.5	10.0	11.0	20/32	3415	50
33X12.50R20LT*	119Q 12PR	RBL	32.8	12.5	8.5	10.0	11.0	20/32	3000	80
35X12.50R20LT*	121Q 10PR	RBL	34.8	12.9	8.5	10.0	11.0	20/32	3195	65
35X12.50R20LT*	125Q 12PR	RBL	34.8	12.9	8.5	10.0	11.0	20/32	3640	80
37X12.50R20LT*	128Q 12PR	RBL	36.8	12.5	8.5	10.0	11.0	20/32	3970	80
37X13.50R20LT*	127Q 10PR	RBL	36.9	14.3	8.5	11.0	11.0	20/32	3860	65
37X13.50R20LT*	128Q 12PR	RBL	36.8	14.3	8.5	11.0	11.0	20/32	3970	80
38X13.50R20LT*	128Q 10PR	RBL	37.7	14.3	9.5	11.0	12.0	20/32	3970	65
40X13.50R20LT*	128Q 10PR	RBL	39.8	14.1	8.5	11.0	11.0	20/32	3970	65
35X12.50R22LT*	121Q 12PR	RBL	34.7	12.5	8.5	10.0	11.0	20/32	3195	80
37X12.50R22LT*	127Q 12PR	RBL	36.8	12.5	9.0	10.0	11.5	20/32	3860	80
37X13.50R22LT*	123Q 10PR	RBL	36.8	13.9	8.5	11.0	11.0	20/32	3415	65
40X15.50R24LT*	128Q 12PR	RBL	40.0	15.5	11.0	12.5	14.0	20/32	3970	80

*3-ply sidewall; RBL - Raised Black Lettering; TBD - To Be Determined

BIGHORN | MT-764

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
LT235/75R15	104/101Q 6PR	RWL	28.9	9.5	6.0	6.5	7.0	19/32	S1985/D1820	50
LT225/75R16	115/112Q 10PR	BSW	29.5	8.8	6.0	6.0	7.0	14/32	S2680/D2470	80
LT225/75R16	115/112Q 10PR	OWL	29.6	8.9	6.0	6.0	7.0	20/32	S2680/D2470	80
LT235/85R16*	120/116N 10PR	BSW	31.8	9.4	6.0	6.5	7.5	19/32	S3042/D2778	80
LT235/85R16*	120/116N 10PR	OWL	31.8	9.4	6.0	6.5	7.5	19/32	S3042/D2778	80
LT245/70R16	113/110Q 8PR	OWL	29.6	9.6	6.5	7.0	7.5	20/32	S2535/D2335	65
LT245/75R16	108/104N 6PR	RWL	30.8	10.0	6.5	7.0	8.0	20/32	S2205/D2005	50
LT245/75R16*	120/116N 10PR	RWL	30.8	10.0	6.5	7.0	8.0	20/32	S3042/D2780	80
LT245/75R16*	120/116N 10PR	OWL	30.8	10.0	6.5	7.0	8.0	20/32	S3042/D2780	80
LT265/70R16	117/114Q 8PR	OWL	30.6	10.5	7.0	8.0	8.5	20/32	S2835/D2600	65
LT265/75R16	112/109N 6PR	RWL	32.0	10.9	7.0	7.5	8.0	20/32	S2470/D2270	50
LT265/75R16*	123/120N 10PR	RWL	32.0	10.7	7.0	7.5	8.0	20/32	S3415/D3085	80
LT265/75R16*	123/120N 10PR	OWL	32.0	10.8	7.0	7.5	8.0	20/32	S3415/D3085	80
LT225/70R17	110/107Q 8PR	BSW	29.5	8.6	6.0	6.5	7.5	19/32	S2340/D2150	65
LT265/65R17	117/114Q 8PR	OWL	30.9	10.7	7.5	8.0	9.5	20/32	S2835/D2600	65
LT265/70R17	118/115Q 8PR	RWL	31.9	10.6	7.0	8.0	8.5	20/32	S2910/D2680	65
LT265/70R17	118/115Q 8PR	OWL	31.9	10.6	7.0	8.0	8.5	20/32	S2910/D2680	65
LT265/60R18	114/110S 8PR	OWL	30.6	10.7	7.5	8.0	9.5	TBD	S2600/D2335	65
LT275/65R18	119/116Q 8PR	BSW	32.2	11.0	7.5	8.0	9.0	20/32	S3000/D2755	65
LT275/65R18	119/116Q 8PR	OWL	32.2	11.0	7.5	8.0	9.0	20/32	S3000/D2755	65
LT275/60R20	119/116Q 8PR	BSW	33.0	11.1	7.5	8.0	9.5	19/32	S3000/D2755	65
LT305/50R20	111/108Q 8PR	BSW	32.2	12.3	8.5	9.5	11.0	20/32	S2405/D2205	50
27X8.50R14LT	95Q 6PR	RWL	26.7	8.8	6.0	7.0	7.5	19/32	1520	50
30X9.50R15LT	104Q 6PR	RWL	29.7	9.8	6.5	7.5	8.5	19/32	1985	50
30X9.50R15LT	104Q 6PR	OWL	29.6	9.8	6.5	7.5	8.5	19/32	1985	50
31X10.50R15LT	109Q 6PR	RWL	30.6	11.1	7.0	8.5	9.0	20/32	2270	50
31X10.50R15LT	109Q 6PR	OWL	30.6	11.1	7.0	8.5	9.0	20/32	2270	50
35X12.50R17LT	113Q 6PR	RWL	32.0	11.8	8.0	9.0	10.0	20/32	2535	50
32X11.50R15LT	113R 6PR	RWL	32.0	11.8	8.0	9.0	10.0	20/32	2535	50
32X11.50R15LT	113R 6PR	OWL	32.0	11.8	8.0	9.0	10.0	20/32	2535	50
33X12.50R15LT	108Q 6PR	RWL	33.0	13.0	8.5	10.0	11.0	20/32	2205	35
33X12.50R15LT	108Q 6PR	OWL	32.0	13.0	8.5	10.0	11.0	20/32	2205	35
35X12.50R17LT*	119Q 8PR	RWL	34.9	13.0	8.5	10.0	11.0	21/32	3000	50
195R14C	106/104Q 8PR	BSW	26.2	7.8	5.0	5.5	6.0	17/32	S2095/D1985	65
205R16C	110/108Q 8PR	BSW	28.9	8.2	5.5	6.0	6.5	17/32	S2335/D2205	65



*3-ply sidewall; BSW - Black Sidewall; OWL - Outline White Lettering; RWL - Raised White Lettering TBD - To Be Determined

CREEPY CRAWLER | M8090



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
6.50-16LT	100L 6PR	BSW	29.8	7.9	4.0	4.5	6.0	19/32	1760	45
7.00-16LT	103L 6PR	BSW	31.0	8.4	5.0	5.5	6.5	20/32	1930	45
7.00-16LT	109L 8PR	BSW	31.0	8.4	5.0	5.5	6.5	20/32	2260	60
255/85-16LT	104K 8PR	BSW	33.1	10.0	6.5	7.0	8.0	23/32	1985	35
35X12.50-15LT	113K 6PR	BSW	34.8	13.6	8.5	10.0	11.0	27/32	2535	30
37X12.50-15LT	117K 8PR	BSW	37.0	13.4	8.5	10.0	11.0	27/32	2830	45
37X14.50-15LT	127K 8PR	BSW	37.0	15.3	9.5	12.0	12.5	27/32	3860	45
38X13.00-15LT	128K 8PR	BSW	38.0	13.5	8.5	10.0	11.0	27/32	3970	45
35X12.50-16LT	112K 6PR	BSW	35.2	13.1	8.5	10.0	11.0	27/32	2470	30
37X12.50-16LT	124K 8PR	BSW	36.8	13.4	8.5	10.0	11.0	27/32	3525	45
37X14.50-16LT	126L 8PR	BSW	37.0	14.3	10.0	12.0	12.0	27/32	3750	45
38.5X14.50-16LT	129K 8PR	BSW	38.5	15.3	10.0	12.0	12.0	27/32	4080	45
40X13.50-17LT	123K 8PR	BSW	40.2	14.5	8.5	11.0	11.0	27/32	3420	45
35X12.50-20LT**	121L 10PR	RBL	35.4	12.4	8.5	10.0	11.0	27/32	3195	60
37X12.50-20LT**	126L 10PR	RBL	37.4	13.2	8.5	10.0	11.0	27/32	3750	60

TREPADOR BIAS | M8060



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
35X12.50-15LT	121K 8PR	BSW	35.1	13.2	8.5	10.0	11.0	22/32	3195	45
35X12.50-16LT	120K 8PR	BSW	35.0	13.2	8.5	10.0	11.0	22/32	3085	45
37X12.50-16LT	124K 8PR	BSW	36.8	13.4	8.5	10.0	11.0	22/32	3525	45
35X12.50-17LT	119K 8PR	BSW	34.6	12.6	8.5	10.0	11.0	22/32	3000	45
37X12.50-17LT	124K 10PR	BSW	37.1	13.2	8.5	10.0	11.0	22/32	3525	45
37X13.50-17LT	126L 10PR	BSW	37.3	14.5	8.5	11.0	11.0	22/32	3750	60
40X13.50-17LT	123K 8PR	BSW	40.2	14.3	8.5	11.0	11.0	22/32	3420	45
42X14.50-17LT	121L 6PR	BSW	42.9	15.3	10.0	12.0	12.0	22/32	3195	30
35X12.50-20LT	121K 10PR	BSW	35.1	12.2	8.5	10.0	11.0	22/32	3195	60

TREPADOR COMPETITION | M8060

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
37X12.50-16LT	124K 8PR	BSW	37.0	13.4	8.5	10.0	11.0	23/32	3525	45
37X12.50-17LT	124K 10PR	BSW	37.1	13.2	8.5	10.0	11.0	23/32	3525	45
40X13.50-17LT	123K 8PR	BSW	40.2	14.3	8.5	11.0	11.0	23/32	3420	45
42X14.50-17LT	121L 6PR	BSW	42.9	15.3	10.0	12.0	12.0	22/32	3195	30

TREPADOR RADIAL | M8060

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
205/70R15C	104/102Q 6PR	BSW	26.4	8.3	5.0	6.0	7.0	16/32	S1985/D1875	55
205R16C	110/108Q 8PR	BSW	28.9	8.1	5.5	6.0	6.5	17/32	S2337/D2205	65
LT235/75R15	104/101Q 6PR	BSW	29.0	9.4	6.0	6.5	7.0	19/32	S1985/D1820	50
30X9.50R15LT	104Q 6PR	BSW	29.9	9.8	6.5	7.5	8.5	20/32	1985	50
31X10.50R15LT	109Q 6PR	BSW	30.6	10.8	7.0	8.5	9.0	20/32	2270	50
33X12.50R15LT	108Q 6PR	BSW	32.8	12.4	8.5	10.0	11.0	21/32	2205	35
35X12.50R15LT*	113Q 6PR	BSW	34.6	13.1	8.5	10.0	11.0	21/32	2535	35
35X12.50R16LT*	121Q 8PR	BSW	34.6	13.0	8.5	10.0	11.0	21/32	3195	50
35X12.50R17LT*	119Q 8PR	BSW	34.6	12.6	8.5	10.0	11.0	21/32	3000	50
37X12.50R17LT*	124Q 8PR	BSW	36.9	13.0	8.5	10.0	11.0	21/32	3525	50
40X13.50R17LT*	121Q 6PR	BSW	39.8	14.0	8.5	11.0	11.0	21/32	3195	35
33X13.00R18LT	124Q 10PR	BSW	33.3	13.1	8.5	9.5	11.0	21/32	3530	65
35X13.00R18LT	127Q 10PR	BSW	34.6	13.1	8.5	9.5	11.0	21/32	3860	65
40X13.50R18LT*	129Q 8PR	BSW	39.8	13.8	8.5	11.0	11.0	21/32	4080	50
33X12.00R20LT	121Q 10PR	BSW	33.2	12.2	8.0	9.5	10.5	21/32	3200	65
35X13.00R20LT	121Q 8PR	BSW	35.0	13.1	9.0	9.5	11.5	21/32	3200	50
40X15.50R22LT	127Q 8PR	BSW	39.6	14.8	11.0	12.0	14.0	21/32	3860	50



ARCTIC TREKKER | NP3

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
155/70R13	75T	BSW	21.6	6.1	4.0	4.5	5.0	11/32	853	44
175/70R13	82T	BSW	22.8	6.9	4.5	5.0	6.0	11/32	1047	44
155/65R14	75T	BSW	22.0	6.1	4.5	4.5	5.5	11/32	853	44
175/65R14	82T	BSW	23.0	6.9	5.0	5.0	6.0	11/32	1047	44
175/70R14	88T XL	BSW	23.8	6.9	4.5	5.0	6.0	11/32	1235	50
185/60R14	86T XL	BSW	22.8	7.3	5.0	5.5	6.5	12/32	1168	50
185/65R14	90T XL	BSW	23.5	7.3	5.0	5.5	6.5	12/32	1323	50
185/70R14	88T	BSW	24.3	7.3	4.5	5.5	6.0	12/32	1235	44
175/65R15	88T XL	BSW	23.9	6.9	5.0	5.0	6.0	11/32	1235	50
185/55R15	86T XL	BSW	23.0	7.3	5.0	6.0	6.5	13/32	1168	50
185/60R15	88T XL	BSW	23.7	7.3	5.0	5.5	6.5	13/32	1235	50
185/65R15	92T XL	BSW	24.4	7.3	5.0	5.5	6.5	13/32	1389	50
195/55R15	89T XL	BSW	23.4	7.7	5.5	6.0	7.0	13/32	1279	50
195/60R15	92T XL	BSW	24.2	7.7	5.5	6.0	7.0	13/32	1389	50
195/65R15	95T XL	BSW	25.0	7.7	5.5	6.0	7.0	13/32	1521	50
205/65R15	99T XL	BSW	25.5	8.1	5.5	6.0	7.5	13/32	1709	50
195/55R16	87T	BSW	24.4	7.7	5.5	6.0	7.0	12/32	1201	44



*3-ply sidewall; XL - Extra Load; BSW - Black Sidewall

ARCTIC TREKKER | NP3 CONTINUED



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
205/55R16	94T XL	BSW	24.9	8.1	5.5	6.5	7.5	13/32	1477	50
205/60R16	96T XL	BSW	25.7	8.1	5.5	6.0	7.5	13/32	1565	50
205/65R16	99T XL	BSW	26.5	8.1	5.5	6.0	7.5	12/32	1709	50
215/55R16	97T XL	BSW	25.4	8.5	6.0	7.0	7.5	12/32	1609	50
215/60R16	99T XL	BSW	26.1	8.5	6.0	6.5	7.5	12/32	1709	50
215/65R16	102T XL	BSW	27.0	8.5	6.0	6.5	7.5	13/32	1874	50
225/55R16	99T XL	BSW	25.7	8.9	6.0	7.0	8.0	12/32	1709	50
225/60R16	102T XL	BSW	26.5	8.9	6.0	6.5	8.0	12/32	1874	50
205/50R17	93T XL	BSW	25.2	8.1	5.5	6.5	7.5	12/32	1433	50
215/50R17	95T XL	BSW	25.5	8.5	6.0	7.0	7.5	13/32	1521	50
215/55R17	98T XL	BSW	26.3	8.5	6.0	7.0	7.5	13/32	1653	50
215/60R17	100T XL	BSW	27.2	8.5	6.0	6.5	7.5	13/32	1764	50
225/45R17	94T XL	BSW	25.0	8.9	7.0	7.5	8.5	12/32	1477	50
225/50R17	98T XL	BSW	25.9	8.9	6.0	7.0	8.0	13/32	1653	50
225/55R17	101T XL	BSW	26.9	8.9	6.0	7.0	8.0	12/32	1819	50
235/45R17	97T XL	BSW	25.4	9.3	7.5	8.0	9.0	12/32	1609	50
235/55R17	103T XL	BSW	27.2	9.3	6.5	7.5	8.5	13/32	1929	50

PREMITRA | ICE NORD NSS



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
235/75R15	105T	BSW	28.9	9.3	6.0	6.5	8.0	TBD	2039	44
215/65R16	98T	BSW	27.0	8.5	6.0	6.5	7.5	12/32	1653	44
215/70R16	100T	BSW	27.9	8.5	5.5	6.5	7.0	TBD	1764	44
225/70R16	103T	BSW	28.4	8.9	6.0	6.5	7.5	TBD	1929	44
235/70R16	106T	BSW	29.0	9.3	6.0	7.0	8.0	TBD	2094	44
245/70R16	111T XL	BSW	29.5	9.6	6.5	7.0	8.0	TBD	2403	50
265/70R16	112T	BSW	30.6	10.4	7.0	8.0	9.0	TBD	2469	44
275/70R16	114T	BSW	31.2	10.8	7.0	8.0	9.0	TBD	2601	44
215/60R17	96T	BSW	27.2	8.7	6.0	6.5	7.5	TBD	1565	44
225/60R17	103T XL	BSW	27.6	9.0	6.0	6.5	8.0	TBD	1929	50
225/65R17	102T	BSW	28.5	8.9	6.0	6.5	8.0	12/32	1874	44
235/65R17	108T XL	BSW	29.1	9.3	6.5	7.0	8.5	12/32	2205	50
265/65R17	116T XL	BSW	30.6	10.4	7.5	8.0	9.5	12/32	2756	50
235/55R18	104T XL	BSW	28.1	9.3	6.5	7.5	8.5	TBD	1984	50
235/60R18	107T XL	BSW	29.1	9.3	6.5	7.0	8.5	TBD	2149	50
255/55R18	109T XL	BSW	29.0	10.0	7.0	8.0	9.0	TBD	2271	50

ARCTIC TREKKER | SP02

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
155/65R13	73T	BSW	21.0	6.1	4.5	4.5	5.5	10/32	805	44
175/70R13	82T	BSW	22.8	6.9	4.5	5.0	6.0	11/32	1047	44
155/65R14	75T	BSW	22.0	6.1	4.5	4.5	5.5	10/32	853	44
165/70R14	81T	BSW	23.1	6.5	4.0	5.0	5.5	11/32	1019	44
175/65R14	82T	BSW	23.0	6.9	5.0	5.0	6.0	11/32	1047	44
185/60R14	82T	BSW	22.8	7.3	5.0	5.5	6.5	11/32	1047	44
185/65R14	90T XL	BSW	23.6	7.3	5.0	5.5	6.5	11/32	1323	50
185/70R14	88T	BSW	24.4	7.3	4.5	5.5	6.0	11/32	1235	44
175/65R15	84T	BSW	24.0	6.9	5.0	5.0	6.0	11/32	1102	44
185/55R15	82T	BSW	23.1	7.3	5.0	6.0	6.5	11/32	1047	44
185/60R15	84T	BSW	23.8	7.3	5.0	5.5	6.5	11/32	1102	44
185/65R15	92T XL	BSW	24.6	7.3	5.0	5.5	6.5	11/32	1389	50
195/50R15	82T	BSW	22.8	7.7	5.5	6.0	7.0	11/32	1047	44
195/55R15	89T XL	BSW	23.5	7.7	5.5	6.0	7.0	11/32	1279	50
195/60R15	92T XL	BSW	24.2	7.7	5.5	6.0	7.0	11/32	1389	50
195/65R15	95T XL	BSW	25.1	7.7	5.5	6.0	7.0	11/32	1521	50
205/65R15	94T	BSW	25.6	8.1	5.5	6.0	7.5	11/32	1477	44
195/50R16	84T	BSW	23.7	7.7	5.5	6.0	7.0	10/32	1102	44
195/55R16	91T XL	BSW	24.4	7.7	5.5	6.0	7.0	11/32	1356	50
205/45R16	83T	BSW	23.2	8.1	6.5	7.0	7.5	10/32	1074	44
205/55R16	94T XL	BSW	24.9	8.1	5.5	6.5	7.5	11/32	1477	50
205/60R16	96T XL	BSW	25.7	8.1	5.5	6.0	7.5	11/32	1565	50
205/65R16	95T	BSW	26.5	8.1	5.5	6.0	7.5	11/32	1521	44
215/55R16	97T XL	BSW	25.3	8.5	6.0	7.0	7.5	11/32	1609	50
215/60R16	99T XL	BSW	26.1	8.5	6.0	6.5	7.5	11/32	1709	50
225/55R16	99T XL	BSW	25.9	8.9	6.0	7.0	8.0	11/32	1709	50
205/50R17	93T XL	BSW	25.2	8.1	5.5	6.5	7.5	11/32	1433	50
215/50R17	91T	BSW	25.6	8.5	6.0	7.0	7.5	11/32	1356	44
215/55R17	98T XL	BSW	26.4	8.5	6.0	7.0	7.5	11/32	1653	50
225/45R17	94T XL	BSW	25.1	8.9	7.0	7.5	8.5	11/32	1477	50
225/50R17	98T XL	BSW	25.9	8.9	6.0	7.0	8.0	11/32	1653	50
225/55R17	101T XL	BSW	26.9	8.9	6.0	7.0	8.0	11/32	1819	50
235/45R17	97T XL	BSW	25.4	9.3	7.5	8.0	9.0	11/32	1609	50
235/50R17	100T XL	BSW	27.3	9.3	6.5	7.5	8.5	11/32	1764	50
235/55R17	99S	BSW	27.2	9.3	6.5	7.5	8.5	11/32	1709	44
245/45R17	99S XL	BSW	25.7	9.6	7.5	8.0	9.0	11/32	1709	50
255/45R17	98T	BSW	26.1	10.0	8.0	8.5	9.5	11/32	1653	44
225/40R18	92S XL	BSW	25.2	8.9	7.5	8.0	9.0	11/32	1389	50
225/45R18	95S XL	BSW	26.1	8.9	7.0	7.5	8.5	11/32	1521	50
235/45R18	98T XL	BSW	26.3	9.3	7.5	8.0	9.0	11/32	1653	50



ARCTIC TREKKER | SPO2 CONTINUED

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
235/50R18	97S	BSW	27.3	9.3	6.5	7.5	8.5	11/32	1609	44
245/40R18	93S	BSW	25.6	9.6	8.0	8.5	9.5	11/32	1433	44
245/45R18	100S XL	BSW	26.7	9.6	7.5	8.0	9.0	11/32	1764	50
245/50R18	100T	BSW	27.7	9.6	7.0	7.5	8.5	11/32	1764	44
255/40R18	95T	BSW	26.0	10.0	8.5	9.0	10.0	11/32	1521	44
255/55R18	105S	BSW	29.0	10.0	7.0	8.0	9.0	12/32	2039	44
255/40R19	100S XL	BSW	27.2	10.0	8.5	9.0	10.0	11/32	1764	50

PREMITRA | SPO3



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
155/65R13	73T	BSW	20.9	6.1	4.5	4.5	5.5	10/32	805	44
155/70R13	75T	BSW	21.5	6.1	4.0	4.5	5.0	10/32	853	44
165/70R13	79T	BSW	22.1	6.5	4.0	5.0	5.5	11/32	963	44
175/70R13	82T	BSW	22.7	6.9	4.5	5.0	6.0	11/32	1047	44
165/70R14	81T	BSW	23.1	6.5	4.0	5.0	5.5	11/32	1019	44
175/65R14	82T	BSW	23.0	6.9	5.0	5.0	6.0	11/32	1047	44
175/70R14	84T	BSW	23.6	6.9	4.5	5.0	6.0	11/32	1102	44
185/60R14	82T	BSW	22.8	7.3	5.0	5.5	6.5	11/32	1047	44
185/65R14	86T	BSW	23.5	7.3	5.0	5.5	6.5	11/32	1168	44
185/70R14	88T	BSW	24.2	7.3	4.5	5.5	6.0	11/32	1234	44
175/65R15	84T	BSW	24.0	6.9	5.0	5.0	6.0	11/32	1102	44
185/55R15	82T	BSW	23.0	7.3	5.0	6.0	6.5	10/32	1047	44
185/60R15	84T	BSW	23.7	7.3	5.0	5.5	6.5	11/32	1102	44
185/65R15	88T	BSW	24.5	7.3	5.0	5.5	6.5	11/32	1234	44
195/50R15	82T	BSW	22.7	7.7	5.5	6.0	7.0	10/32	1047	44
195/55R15	85T	BSW	23.4	7.7	5.5	6.0	7.0	11/32	1135	44
195/60R15	88T	BSW	24.2	7.7	5.5	6.0	7.0	11/32	1235	44
195/65R15	91T	BSW	25.0	7.7	5.5	6.0	7.0	11/32	1355	44
205/60R15	91T	BSW	24.7	8.1	5.5	6.0	7.5	11/32	1356	44
205/65R15	94T	BSW	25.5	8.1	5.5	6.0	7.5	11/32	1477	44
195/55R16	87T	BSW	24.4	7.7	5.5	6.0	7.0	11/32	1201	44
195/60R16	89T	BSW	25.2	7.7	5.5	6.0	7.0	11/32	1279	44
205/55R16	91T	BSW	24.9	8.1	5.5	6.5	7.5	11/32	1355	44
205/60R16	92T	BSW	25.7	8.1	5.5	6.0	7.5	11/32	1388	44
205/65R16	95T	BSW	26.5	8.1	5.5	6.0	7.5	11/32	1521	44

PRESA | ICE SUV SS-01

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
205/70R15	96Q	BSW	26.3	8.1	5.0	6.0	7.0	14/32	1565	44
215/70R15	98Q	BSW	26.9	8.5	5.5	6.5	7.0	14/32	1653	44
215/75R15	100Q	BSW	27.8	8.5	5.5	6.0	7.0	14/32	1764	44
235/75R15	105Q	BSW	28.9	9.3	6.0	6.5	8.0	14/32	2039	44
265/70R15	112Q	BSW	29.6	10.4	7.0	8.0	9.0	14/32	2469	44
175/80R16	91Q	BSW	27.1	6.9	5.0	5.0	5.0	13/32	1356	44
215/65R16	98Q	BSW	27.1	8.5	6.0	6.5	7.5	14/32	1653	44
215/70R16	100Q	BSW	27.9	8.5	5.5	6.5	7.0	14/32	1764	44
225/70R16	103Q	BSW	28.4	8.9	6.0	6.5	7.5	14/32	1929	44
235/60R16	100Q	BSW	27.2	9.3	6.5	7.0	8.5	14/32	1764	44
235/70R16	106Q	BSW	29.0	9.3	6.0	7.0	8.0	14/32	2094	44
245/70R16	107Q	BSW	29.6	9.6	6.5	7.0	8.0	14/32	2149	44
245/75R16	111Q	BSW	30.5	9.6	6.5	7.0	8.0	14/32	2403	44
255/65R16	109Q	BSW	29.1	10.0	7.0	7.5	9.0	14/32	2271	44
265/70R16	112Q	BSW	30.6	10.4	7.0	8.0	9.0	14/32	2469	44
275/70R16	114Q	BSW	31.2	10.8	7.0	8.0	9.0	14/32	2601	44
215/60R17	96Q	BSW	27.1	8.5	6.0	6.5	7.5	14/32	1565	44
225/60R17	99T	BSW	27.6	8.9	6.0	6.5	8.0	14/32	1709	44
225/65R17	102Q	BSW	28.6	8.9	6.0	6.5	8.0	14/32	1874	44
235/65R17	108Q XL	BSW	29.1	9.3	6.5	7.0	8.5	14/32	2205	50
245/65R17	107Q	BSW	29.6	9.6	7.0	7.0	8.5	14/32	2150	44
255/60R17	106Q	BSW	29.1	10.0	7.0	7.5	9.0	14/32	2094	44
265/65R17	112Q	BSW	30.6	10.4	7.5	8.0	9.5	14/32	2469	44
275/65R17	115Q	BSW	31.2	10.8	7.5	8.0	9.5	14/32	2679	44
285/65R17	116Q	BSW	31.7	11.2	8.0	8.5	10.0	14/32	2756	44
215/55R18	99Q XL	BSW	27.3	8.5	6.0	7.0	7.5	14/32	1709	50
225/55R18	102Q XL	BSW	27.8	8.9	6.0	7.0	8.0	14/32	1874	50
225/60R18	100T	BSW	28.5	8.9	6.0	6.5	8.0	14/32	1764	44
235/55R18	100Q	BSW	28.1	9.3	6.5	7.5	8.5	14/32	1764	44
235/60R18	103Q	BSW	29.2	9.3	6.5	7.0	8.5	14/32	1929	44
245/60R18	105Q	BSW	29.6	9.6	7.0	7.0	8.5	14/32	2039	44
255/55R18	109T XL	BSW	29.0	10.0	7.0	8.0	9.0	14/32	2270	50
255/60R18	112T XL	BSW	30.0	10.0	7.0	7.5	9.0	14/32	2469	50
265/60R18	110Q	BSW	30.5	10.4	7.5	8.0	9.5	14/32	2337	44
285/60R18	116Q	BSW	31.5	11.2	8.0	8.5	10.0	14/32	2756	44
235/55R19	105Q XL	BSW	29.3	9.3	6.5	7.5	8.5	14/32	2039	50
245/55R19	103T	BSW	29.8	9.6	7.0	7.5	8.5	14/32	1929	44
255/50R19	107T XL	BSW	29.3	10.0	7.0	8.0	9.0	14/32	2149	50
255/55R19	111R XL	BSW	30.2	10.0	7.0	8.0	9.0	14/32	2403	50
265/50R19	110Q XL	BSW	29.5	10.4	7.5	8.5	9.5	14/32	2337	50



PRESA | ICE SUV SS-01 CONTINUED

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
275/45R19	108R XL	BSW	28.9	10.8	8.5	9.0	10.5	14/32	2205	50
275/55R19	111Q	BSW	30.9	10.8	7.5	8.5	9.5	14/32	2403	44
255/50R20	109Q XL	BSW	30.1	10.0	7.0	8.0	9.0	14/32	2271	50
275/40R20	106R XL	BSW	28.7	10.8	9.0	9.5	11.0	14/32	2094	50
275/45R20	110T XL	BSW	29.9	10.8	8.5	9.0	10.5	14/32	2337	50

ARCTIC TREKKER | AP2



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
145/70R13	71T	BSW	21.1	6.0	3.5	4.5	5.0	10/32	761	44
145/80R13	79T XL	BSW	22.4	5.7	3.5	4.0	5.0	10/32	963	50
155/65R13	73T	BSW	21.1	5.9	4.5	4.5	5.5	10/32	805	44
155/70R13	75T	BSW	21.6	6.1	4.0	4.5	5.0	10/32	853	44
155/80R13	83T XL	BSW	22.9	6.3	4.0	4.5	5.0	10/32	1074	50
165/65R13	77T	BSW	21.5	6.5	4.5	5.0	6.0	10/32	908	44
165/70R13	83T XL	BSW	22.2	6.5	4.0	5.0	5.5	10/32	1074	50
165/80R13	87T XL	BSW	23.5	6.5	4.0	4.5	5.5	10/32	1201	50
175/65R13	80T	BSW	22.1	6.8	5.0	5.0	6.0	11/32	992	44
175/70R13	82T	BSW	22.7	6.9	4.5	5.0	6.0	10/32	1047	44
185/70R13	86T	BSW	23.3	7.6	4.5	5.5	6.0	11/32	1168	44
155/65R14	79T XL	BSW	22.0	6.1	4.5	4.5	5.5	10/32	963	50
165/60R14	79H XL	BSW	22.0	6.5	4.5	5.0	6.0	11/32	963	50
165/65R14	83T XL	BSW	22.6	6.5	4.5	5.0	6.0	10/32	1074	50
165/70R14	85T XL	BSW	23.3	6.8	4.0	5.0	5.5	10/32	1135	50
175/60R14	79H	BSW	22.4	6.9	5.0	5.0	6.0	11/32	963	44
175/65R14	86H XL	BSW	25.1	6.9	5.0	5.0	6.0	11/32	1168	50
175/70R14	88T XL	BSW	23.7	6.9	4.5	5.0	6.0	10/32	1235	50
175/80R14	88H	BSW	25.1	7.1	4.5	5.0	6.0	10/32	1235	44
175/80R14	88T	BSW	25.1	7.1	4.5	5.0	6.0	10/32	1235	44
185/55R14	80H	BSW	22.1	7.3	5.0	6.0	6.5	10/32	992	44
185/60R14	82H	BSW	22.8	7.3	5.0	5.5	6.5	11/32	1047	44
185/65R14	86H	BSW	23.5	7.4	5.0	5.5	6.5	11/32	1168	44
185/70R14	92H XL	BSW	24.4	7.5	4.5	5.5	6.0	11/32	1389	50
195/60R14	86H	BSW	23.2	7.9	5.5	6.0	7.0	11/32	1168	44
195/65R14	93H XL	BSW	24.0	7.7	5.5	6.0	7.0	11/32	1433	50

ARCTIC TREKKER | AP2 CONTINUED

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
195/65R14	89H	BSW	24.0	7.9	5.5	6.0	7.0	11/32	1279	44
135/80R15	73T	BSW	23.6	5.2	3.5	3.5	4.5	10/32	805	44
145/65R15	72T	BSW	22.5	5.8	4.0	4.5	5.0	10/32	783	44
155/60R15	74T	BSW	22.4	6.0	4.5	4.5	5.5	11/32	827	44
165/60R15	77T	BSW	22.9	6.6	4.5	5.0	6.0	11/32	908	44
165/65R15	81T	BSW	23.5	6.5	4.5	5.0	6.0	10/32	1019	44
175/55R15	77T	BSW	22.6	7.1	5.0	5.5	6.0	10/32	908	44
175/60R15	81H	BSW	23.3	6.9	5.0	5.0	6.0	11/32	1019	44
175/65R15	88H XL	BSW	24.0	6.9	5.0	5.0	6.0	11/32	1235	50
185/55R15	86V XL	BSW	23.1	7.3	5.0	6.0	6.5	10/32	1168	50
185/60R15	88H XL	BSW	23.7	7.3	5.0	5.5	6.5	11/32	1235	50
185/65R15	92H XL	BSW	24.5	7.3	5.0	5.5	6.5	11/32	1389	50
195/50R15	86V XL	BSW	22.9	7.8	5.5	6.0	7.0	11/32	1168	50
195/55R15	89V XL	BSW	23.6	7.8	5.5	6.0	7.0	10/32	1279	50
195/60R15	88H	BSW	24.2	7.7	5.5	6.0	7.0	11/32	1235	44
195/65R15	91H	BSW	25.0	8.0	5.5	6.0	7.0	11/32	1356	44
195/65R15	95H XL	BSW	25.0	7.7	5.5	6.0	7.0	11/32	1521	50
205/50R15	89V XL	BSW	23.3	8.1	5.5	6.5	7.5	11/32	1279	50
205/55R15	88V	BSW	24.0	8.1	5.5	6.5	7.5	11/32	1235	44
205/60R15	95H XL	BSW	24.8	8.2	5.5	6.0	7.5	11/32	1521	50
205/65R15	100H XL	BSW	25.6	8.1	5.5	6.0	7.5	11/32	1764	50
215/65R15	100H XL	BSW	26.0	8.7	6.0	6.5	7.5	11/32	1764	50
185/50R16	81V	BSW	23.4	7.3	5.0	6.0	6.5	11/32	1019	44
185/55R16	87H XL	BSW	24.2	7.5	5.0	6.0	6.5	10/32	1201	50
195/45R16	84V XL	BSW	22.9	7.7	6.0	6.5	7.5	11/32	1102	50
195/50R16	88V XL	BSW	23.7	7.7	5.5	6.0	7.0	11/32	1235	50
195/55R16	91V XL	BSW	24.4	7.7	5.5	6.0	7.0	11/32	1356	50
205/45R16	87V XL	BSW	23.2	8.1	6.5	7.0	7.5	11/32	1201	50
205/50R16	87V	BSW	24.3	8.4	5.5	6.5	7.5	11/32	1201	44
205/55R16	94V XL	BSW	24.9	8.1	5.5	6.5	7.5	11/32	1477	50
205/55R16	91H	BSW	25.0	8.1	5.5	6.5	7.5	11/32	1356	44
205/60R16	96V XL	BSW	25.8	8.2	5.5	6.0	7.5	11/32	1565	50
215/45R16	90V XL	BSW	23.7	8.4	7.0	7.0	8.0	11/32	1323	50
215/55R16	97V XL	BSW	25.3	8.9	6.0	7.0	7.5	11/32	1609	50
215/60R16	99H XL	BSW	26.1	8.7	6.0	6.5	7.5	11/32	1709	50
215/65R16	102H XL	BSW	27.0	8.5	6.0	6.5	7.5	11/32	1874	50
225/50R16	96V XL	BSW	25.0	9.2	6.0	7.0	8.0	11/32	1565	50
225/55R16	99V XL	BSW	25.8	9.1	6.0	7.0	8.0	11/32	1709	50
225/60R16	102V XL	BSW	26.5	9.1	6.0	6.5	8.0	11/32	1874	50
205/40R17	84V XL	BSW	23.3	8.4	7.0	7.5	8.0	10/32	1102	50



ARCTIC TREKKER | AP2 CONTINUED



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
205/45R17	88V XL	BSW	24.3	8.1	6.5	7.0	7.5	11/32	1235	50
205/50R17	93V XL	BSW	25.2	8.1	5.5	6.5	7.5	11/32	1433	50
205/55R17	95V XL	BSW	26.0	8.4	5.5	6.5	7.5	11/32	1521	50
215/40R17	87V XL	BSW	23.6	8.6	7.0	7.5	8.5	11/32	1201	50
215/45R17	91V XL	BSW	24.6	8.5	7.0	7.0	8.0	11/32	1356	50
215/50R17	95V XL	BSW	25.6	8.5	6.0	7.0	7.5	11/32	1521	50
215/55R17	98V XL	BSW	26.3	8.5	6.0	7.0	7.5	11/32	1653	50
215/60R17	96H	BSW	27.2	8.5	6.0	6.5	7.0	TBD	1565	44
215/65R17	99V	BSW	28.0	8.5	6.0	6.5	7.0	TBD	1709	44
225/45R17	94V XL	BSW	25.1	8.8	7.0	7.5	8.5	11/32	1477	50
225/50R17	98V XL	BSW	26.1	9.1	6.0	7.0	8.0	11/32	1653	50
225/55R17	101V XL	BSW	26.8	8.9	6.0	7.0	8.0	11/32	1819	50
225/60R17	99V	BSW	27.6	8.9	6.0	6.5	8.0	11/32	1709	44
225/65R17	102H	BSW	28.5	8.9	6.0	6.5	7.0	TBD	1874	44
235/45R17	97V XL	BSW	25.4	9.2	7.5	8.0	9.0	11/32	1609	50
235/55R17	103V XL	BSW	27.2	9.3	7.0	7.5	8.0	TBD	1929	50
235/60R17	106H XL	BSW	28.1	9.3	6.5	7.0	7.5	TBD	2094	50
235/65R17	108V XL	BSW	29.1	9.3	6.5	7.0	7.5	TBD	2205	50
245/45R17	99V XL	BSW	25.6	9.6	7.5	8.0	9.0	11/32	1709	50
215/55R18	95V	BSW	27.5	8.7	6.0	7.0	7.5	11/32	1521	44
215/55R18	99V XL	BSW	27.3	8.5	6.5	7.0	7.5	TBD	1709	50
225/40R18	92V XL	BSW	24.9	9.1	7.5	8.0	9.0	11/32	1389	50
225/45R18	95V XL	BSW	26.1	8.7	7.0	7.5	8.5	11/32	1521	50
225/55R18	98V	BSW	28.0	9.1	6.0	7.0	8.0	11/32	1653	44
235/40R18	95V XL	BSW	25.2	9.5	8.0	8.5	9.5	11/32	1521	50
235/50R18	97V	BSW	27.3	9.3	7.0	7.5	8.0	TBD	1609	44
235/60R18	107V XL	BSW	29.1	9.3	6.5	7.0	7.5	11/32	2149	50
235/65R18	110H XL	BSW	30.0	9.3	6.5	7.0	7.5	TBD	2337	50
245/40R18	97V XL	BSW	25.7	9.6	8.0	8.5	9.5	11/32	1609	50
245/45R18	100V XL	BSW	26.7	9.5	7.5	8.0	9.0	11/32	1764	50
255/55R18	109V XL	BSW	29.0	10.0	7.5	8.0	8.5	TBD	2271	50
255/60R18	112V XL	BSW	30.0	10.0	7.0	7.5	8.0	TBD	2469	50
265/60R18	110H	BSW	30.5	10.4	7.5	8.0	8.5	TBD	2337	44
225/45R19	96V XL	BSW	27.2	8.7	7.0	7.5	8.5	11/32	1565	50
235/55R19	101V	BSW	29.2	9.3	7.0	7.5	8.0	TBD	1819	44
255/50R19	107W XL	BSW	29.1	10.0	7.5	8.0	8.5	TBD	2149	50
255/45R20	105W XL	BSW	29.1	10.0	8.0	8.5	9.0	TBD	2039	50
275/45R20	110W XL	BSW	29.8	10.8	8.5	9.0	9.5	TBD	2337	50

VANSMART A/S | AL2

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
175R14C	99/98R 8PR	BSW	25.1	7.1	4.5	5.0	5.5	12/32	S1710/D1655	65
185R14C	102/100R 8PR	BSW	25.7	7.5	5.0	5.5	6.0	12/32	S1875/D1765	65
195R14C	106/104R 8PR	BSW	26.5	7.6	5.0	5.5	6.0	13/32	S2095/D1985	65
165/70R14C	89/87R 6PR	BSW	23.4	6.5	4.5	5.0	5.0	12/32	S1280/D1200	54
175/70R14C	95/93T 6PR	BSW	23.9	6.8	4.5	5.0	5.5	12/32	S1520/D1435	54
195/70R15C	104/102R 8PR	BSW	25.9	7.9	5.0	6.0	6.0	12/32	S1985/D1875	65
205/65R15C	102/100T 6PR	BSW	25.6	8.1	5.5	6.0	6.5	13/32	S1875/D1765	54
205/70R15C	106/104R 8PR	BSW	26.5	8.1	5.5	6.0	6.5	13/32	S2095/D1985	65
215/65R15C	104/102T 6PR	BSW	26.1	8.7	6.0	6.5	7.0	13/32	S1985/D1875	54
215/70R15C	109/107T 8PR	BSW	27.0	8.7	5.5	6.5	7.0	13/32	S2270/D2150	65
225/70R15C	112/110R 8PR	BSW	27.5	8.9	6.0	6.5	7.0	13/32	S2470/D2335	65
185/75R16C	104/102R 8PR	BSW	27.1	7.1	5.0	5.0	6.0	12/32	S1985/D1875	69
195/60R16C	99/97T 6PR	BSW	25.4	7.8	5.5	6.0	6.5	12/32	S1710/D1610	54
195/65R16C	104/102T 8PR	BSW	26.1	7.8	5.5	6.0	6.0	13/32	S1985/D1875	69
195/75R16C	107/105R 8PR	BSW	27.6	7.8	5.0	5.5	6.0	12/32	S2150/D2040	69
205/60R16C	100/98T 6PR	BSW	25.9	8.1	6.0	6.0	6.5	13/32	S1765/D1655	54
205/65R16C	107/105T 8PR	BSW	26.7	8.1	5.5	6.0	6.5	12/32	S2150/D2040	69
205/75R16C	113/111R 10PR	BSW	28.3	8.0	5.5	6.0	6.5	13/32	S2535/D2405	76
215/60R16C	103/101T 6PR	BSW	26.4	8.4	6.0	6.5	6.5	13/32	S1930/D1820	54
215/65R16C	109/107T 8PR	BSW	27.2	8.6	6.0	6.5	7.0	13/32	S2270/D2150	69
215/70R16C	108/106T 6PR	BSW	28.0	8.7	5.5	6.5	7.0	13/32	S2205/D2095	54
215/75R16C	116/114R 10PR	BSW	28.8	8.5	5.5	6.0	7.0	13/32	S2755/D2600	76
225/65R16C	112/110T 8PR	BSW	27.8	8.9	6.0	6.5	7.0	13/32	S2470/D2335	69
225/75R16C	121/120R 10PR	BSW	29.4	8.9	6.0	6.0	7.0	13/32	S3195/D3085	84
235/65R16C	115/113T 8PR	BSW	28.2	9.5	6.5	7.0	7.5	12/32	S2680/D2535	69
215/60R17C	109/107H 8PR	BSW	27.3	8.5	6.0	6.5	7.0	13/32	S2270/D2150	69
225/55R17C	109/107H 8PR	BSW	27.1	9.2	6.5	7.0	7.5	12/32	S2270/D2150	69



ARCTIC TREKKER | WPO5

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
145/70R12	69T	BSW	20.1	5.7	3.5	4.5	5.0	11/32	716	44
145/70R13	71T	BSW	21.1	5.7	3.5	4.5	5.0	10/32	761	44
145/80R13	79T XL	BSW	22.2	5.8	3.5	4.0	5.0	10/32	963	50
155/65R13	73T	BSW	21.1	6.0	4.5	4.5	5.5	11/32	805	44
155/70R13	75T	BSW	21.6	6.1	4.0	4.5	5.0	10/32	853	44
155/80R13	83T XL	BSW	22.8	6.3	4.0	4.5	5.0	10/32	1074	50
165/70R13	83T XL	BSW	22.2	6.6	4.0	5.0	5.5	10/32	1074	50



ARCTIC TREKKER | WPOS CONTINUED



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
165/80R13	87T XL	BSW	23.4	6.5	4.0	4.5	5.5	10/32	1201	50
175/65R13	80T	BSW	22.1	6.9	5.0	5.0	6.0	11/32	992	44
175/70R13	82T	BSW	22.8	6.9	4.5	5.0	6.0	11/32	1047	44
155/65R14	79T XL	BSW	22.0	6.1	4.5	4.5	5.5	10/32	963	50
165/60R14	79T XL	BSW	21.9	6.6	4.5	5.0	6.0	11/32	963	50
165/65R14	83T XL	BSW	22.5	6.5	4.5	5.0	6.0	11/32	1074	50
175/65R14	82T	BSW	23.1	6.9	5.0	5.0	6.0	11/32	1047	44
185/55R14	80H	BSW	21.9	7.7	5.0	6.0	6.5	10/32	992	44
195/60R14	86H	BSW	23.4	7.8	5.5	6.0	7.0	11/32	1168	44
195/65R14	93T XL	BSW	24.0	7.7	5.5	6.0	7.0	11/32	1433	50
135/70R15	70T	BSW	22.5	5.3	4.0	4.0	4.0	10/32	739	44
145/65R15	72T	BSW	22.5	5.7	4.0	4.5	5.0	10/32	783	44
155/60R15	74T	BSW	22.4	6.1	4.5	4.5	5.5	11/32	827	44
165/60R15	81T XL	BSW	22.9	6.5	4.5	5.0	6.0	11/32	1019	50
165/65R15	81T	BSW	23.5	6.5	4.5	5.0	6.0	11/32	1019	44
175/60R15	81T	BSW	23.5	6.7	5.0	5.0	6.0	11/32	1019	44
175/65R15	88T XL	BSW	24.1	6.7	5.0	5.0	6.0	11/32	1235	50
185/55R15	86H XL	BSW	23.0	7.7	5.0	6.0	6.5	10/32	1168	50
195/50R15	86H XL	BSW	22.7	7.7	5.5	6.0	7.0	11/32	1168	50
195/60R15	88T	BSW	24.3	7.8	5.5	6.0	7.0	11/32	1235	44
195/65R15	91T	BSW	25.0	7.8	5.5	6.0	7.0	11/32	1356	44
195/65R15	95T XL	BSW	25.1	7.8	5.5	6.0	7.0	11/32	1521	50
195/65R15	91H	BSW	25.0	7.8	5.5	6.0	7.0	11/32	1356	44
205/65R15	99T XL	BSW	25.4	8.1	5.5	6.0	7.5	11/32	1709	50
205/65R15	99H XL	BSW	25.4	8.1	5.5	6.0	7.5	11/32	1709	50
215/65R15	100H XL	BSW	26.0	8.5	6.0	6.5	7.5	11/32	1764	50
185/50R16	81V	BSW	23.3	7.4	5.0	6.0	6.5	11/32	1019	44
185/55R16	87H XL	BSW	23.9	7.6	5.0	6.0	6.5	11/32	1201	50
195/45R16	84V XL	BSW	23.1	7.5	6.0	6.5	7.5	11/32	1102	50
195/50R16	88V XL	BSW	23.7	7.6	5.5	6.0	7.0	11/32	1235	50
195/55R16	87H	BSW	24.4	7.9	5.5	6.0	7.0	11/32	1201	44
205/45R16	87H XL	BSW	23.3	8.2	6.5	7.0	7.5	11/32	1201	50
205/55R16	91T	BSW	24.8	9.1	5.5	6.5	7.5	11/32	1356	44
205/55R16	91H	BSW	24.8	8.4	5.5	6.5	7.5	11/32	1356	44
205/55R16	94V XL	BSW	24.8	8.4	5.5	6.5	7.5	11/32	1477	50
205/60R16	96H XL	BSW	25.7	8.1	5.5	6.0	7.5	11/32	1565	50
215/55R16	97H XL	BSW	25.2	8.5	6.0	7.0	7.5	11/32	1609	50
215/60R16	99H XL	BSW	26.3	8.6	6.0	6.5	7.5	11/32	1709	50
225/55R16	99H XL	BSW	25.7	8.9	6.0	7.0	8.0	11/32	1709	50
225/60R16	102H XL	BSW	26.7	8.8	6.0	6.5	8.0	12/32	1874	50

ARCTIC TREKKER | WPOS CONTINUED

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
205/40R17	84V XL	BSW	23.4	8.4	7.0	7.5	8.0	11/32	1102	50
205/45R17	88V XL	BSW	24.4	8.3	6.5	7.0	7.5	11/32	1235	50
205/50R17	93V XL	BSW	25.2	8.2	5.5	6.5	7.5	11/32	1433	50
205/55R17	91H	BSW	25.9	8.3	5.5	6.5	7.5	11/32	1356	44
215/40R17	87V XL	BSW	23.8	8.6	7.0	7.5	8.5	11/32	1201	50
215/45R17	91V XL	BSW	24.6	8.2	7.0	7.0	8.0	11/32	1356	50
215/50R17	95V XL	BSW	25.6	8.6	6.0	7.0	7.5	11/32	1521	50
225/45R17	94V XL	BSW	24.9	8.7	7.0	7.5	8.5	11/32	1477	50
225/50R17	98V XL	BSW	25.9	8.9	6.0	7.0	8.0	12/32	1653	50
225/55R17	101V XL	BSW	26.8	9.0	6.0	7.0	8.0	11/32	1819	50
235/45R17	97V XL	BSW	25.3	9.4	7.5	8.0	9.0	11/32	1609	50
225/40R18	92V XL	BSW	25.1	9.0	7.5	8.0	9.0	12/32	1389	50
225/60R18	104V XL	BSW	TBD	TBD	6.0	6.5	8.0	12/32	1984	50



VANSMART SNOW | WL2

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
155R12C	88/86R 8PR	BSW	21.9	6.0	4.0	4.5	5.0	11/32	S1235/D1170	65
165R13C	91/89R 6PR	BSW	23.5	6.4	4.0	4.5	5.0	11/32	S1355/D1280	54
175R14C	99/98R 6PR	BSW	25.0	7.0	4.5	5.0	5.5	11/32	S1710/D1655	65
185R14C	102/100R 6PR	BSW	25.7	7.4	5.0	5.5	6.0	13/32	S1875/D1765	65
195R14C	106/104R 6PR	BSW	26.3	7.8	5.0	5.5	6.0	13/32	S2095/D1985	65
205R14C	109/107R 6PR	BSW	27.1	8.3	5.5	6.0	6.5	13/32	S2270/D2150	65
185R15C	103/102R 6PR	BSW	26.6	7.4	5.0	5.5	6.0	13/32	S1930/D1875	65
165/70R14	89/87R 6PR	BSW	23.0	6.6	4.5	5.0	5.0	11/32	S1280/D1200	54
175/65R14	90/88T 6PR	BSW	23.0	7.0	5.0	5.0	5.5	12/32	S1325/D1235	54
175/70R14	95/93T 6PR	BSW	23.5	6.9	4.5	5.0	5.5	11/32	S1520/D1435	54
185/75R14	102/100R 6PR	BSW	25.1	7.2	5.0	5.0	6.0	13/32	S1875/D1765	69
185/60R15	94/92T 6PR	BSW	23.9	7.2	5.5	6.0	6.0	13/32	S1475/D1390	54
195/70R15	104/102R 6PR	BSW	25.7	7.9	5.0	6.0	6.0	13/32	S1985/D1875	65
205/65R15	102/100T 6PR	BSW	25.6	8.2	5.5	6.0	6.5	13/32	S1875/D1765	54
205/70R15	106/104R 6PR	BSW	26.2	8.2	5.5	6.0	6.5	13/32	S2095/D1985	65
215/65R15	104/102T 6PR	BSW	26.1	8.7	6.0	6.5	7.0	13/32	S1985/D1875	54
215/70R15	109/107R 6PR	BSW	26.7	8.8	5.5	6.5	7.0	13/32	S2270/D2150	65
225/70R15	112/110R 6PR	BSW	27.4	9.1	6.0	6.5	7.0	13/32	S2470/D2335	65
175/75R16	101/99R 8PR	BSW	26.5	6.9	4.5	5.0	5.5	11/32	S1820/D1710	69
185/75R16	104/102R 8PR	BSW	27.1	7.1	5.0	5.0	6.0	13/32	S1985/D1875	69
195/60R16	99/97T 6PR	BSW	25.4	7.8	5.5	6.0	6.5	13/32	S1710/D1610	54



VANSMART SNOW | WL2 CONTINUED



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
195/65R16	104/102T 6PR	BSW	26.1	7.8	5.5	6.0	6.0	13/32	S1985/D1875	69
195/75R16	107/105R 8PR	BSW	27.7	7.6	5.0	5.5	6.0	13/32	S2150/D2040	69
205/60R16	100/98T 6PR	BSW	25.9	8.0	6.0	6.0	6.5	13/32	S1765/D1655	54
205/65R16	107/105T 6PR	BSW	26.6	8.1	5.5	6.0	6.5	13/32	S2150/D2040	69
205/75R16	110/108R 8PR	BSW	28.3	7.9	5.5	5.5	6.5	13/32	S2335/D2205	69
205/75R16	113/111R 10PR	BSW	28.1	8.1	5.5	5.5	6.5	13/32	S2535/D2405	76
215/60R16	103/101T 6PR	BSW	26.4	8.5	6.0	6.5	6.5	13/32	S1930/D1820	54
215/65R16	109/107T 6PR	BSW	27.1	8.7	6.0	6.5	7.0	13/32	S2270/D2150	69
215/70R16	108/106T 6PR	BSW	27.8	8.7	5.5	6.5	7.0	13/32	S2250/D2095	54
215/75R16	113/111R 8PR	BSW	28.9	8.5	5.5	6.0	7.0	13/32	S2535/D2405	69
225/65R16	112/110R 6PR	BSW	27.6	8.9	6.0	6.5	7.0	13/32	S2470/D2335	69
225/75R16	118/116R 10PR	BSW	29.4	8.9	6.0	6.0	7.0	13/32	S2910/D2755	76
235/65R16	115/113R 6PR	BSW	28.1	9.4	6.5	7.0	7.5	13/32	S2680/D2535	69
215/60R17	109/107H 8PR	BSW	27.4	8.5	6.0	6.5	7.0	13/32	S2270/D2150	69
225/55R17	109/107H 8PR	BSW	27.0	9.2	6.5	7.0	7.5	13/32	S2270/D2150	69

PRESA SPIKE | MA-SLW



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
165/70R14C	89/87Q 6PR	BSW	23.2	6.5	4.5	5.0	5.0	12/32	S1279/D1200	54
175/65R14C	90/88Q 6PR	BSW	23.0	6.9	5.0	5.0	5.5	12/32	S1323/D1235	54
205/65R15C	102/100Q 6PR	BSW	25.6	8.1	5.5	6.0	6.5	14/32	S1874/D1765	54
205/70R15C	106/104Q 8PR	BSW	26.4	8.1	5.5	6.0	6.5	14/32	S2094/D1985	65
215/70R15C	109/107Q 8PR	BSW	26.9	8.5	5.5	6.5	7.0	14/32	S2270/D2150	65
215/75R15C	106/103Q 8PR	BSW	27.7	8.5	5.5	6.0	7.0	14/32	S2094/D1930	65
225/70R15C	112/110Q 8PR	BSW	27.4	8.9	6.0	6.5	7.0	15/32	S2470/D2335	65
225/75R15C	108/104Q 8PR	BSW	28.4	8.9	6.0	6.0	7.0	14/32	S2205/D1985	65
195/60R16C	99/97Q 6PR	BSW	25.2	7.7	5.5	6.0	6.5	14/32	S1710/D1610	54
195/65R16C	104/102Q 8PR	BSW	26.1	7.7	5.5	6.0	6.0	14/32	S1985/D1875	69
195/75R16C	107/105Q 8PR	BSW	27.5	7.7	5.0	5.5	6.0	14/32	S2150/D2040	69
205/60R16C	100/98Q 6PR	BSW	25.7	8.1	6.0	6.0	6.5	14/32	S1765/D1655	54
205/65R16C	107/105Q 8PR	BSW	26.5	8.1	5.5	6.0	6.5	14/32	S2150/D2040	69
215/65R16C	109/107Q 8PR	BSW	27.0	8.5	6.0	6.5	7.0	14/32	S2265/D2145	69
215/75R16C	116/114Q 10PR	BSW	28.7	8.5	5.5	6.0	7.0	14/32	S2760/D2605	76
225/65R16C	112/110Q 8PR	BSW	27.5	8.9	6.0	6.5	7.0	14/32	S2470/D2335	69
235/65R16C	115/113Q 8PR	BSW	28.0	9.3	6.5	7.0	7.5	14/32	S2680/D2535	69
155R12C	88/86Q 8PR	BSW	21.7	6.1	4.0	4.5	5.0	12/32	S1235/D1170	65
155R13C	85/83Q 6PR	BSW	22.8	6.1	4.0	4.5	5.0	12/32	S1135/D1075	54

PRESA SPIKE | MA-SLW CONTINUED

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
165R13C	94/93Q 8PR	BSW	23.5	6.5	4.0	4.5	5.0	12/32	S1475/D1435	65
175R13C	97/95Q 8PR	BSW	24.1	6.9	4.5	5.0	5.5	12/32	S1610/D1520	65
185R14C	102/100Q 8PR	BSW	25.6	7.3	5.0	5.5	6.0	14/32	S1875/D1765	65
195R14C	106/104Q 8PR	BSW	26.2	7.7	5.0	5.5	6.0	14/32	S2095/D1985	65
205R14C	109/107Q 8PR	BSW	27.0	8.1	5.5	5.5	6.5	14/32	S2270/D2150	65
205R16C	110/108Q 8PR	BSW	29.0	8.1	5.5	5.5	6.5	14/32	S2335/D2205	65

BRAVO | UE-168(N)

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
LT5.00R12	83/81P 8PR	BSW	22.4	5.5	3.5	3.5	4.5	11/32	S1070/D1025	65
LT5.50R12	92/90P 10PR	BSW	23.6	6.3	4.0	3.5	5.5	11/32	S1389/D1323	73
LT5.50R13	94/92P 10PR	BSW	24.6	6.3	4.0	3.5	5.5	11/32	S1480/D1410	80
LT5.50R13	97/95P 12PR	BSW	24.7	6.4	4.0	3.5	5.5	11/32	S1610/D1520	91
LT235/75R15	110/107Q 8PR	BSW	28.9	9.6	6.0	6.5	7.0	14/32	S2337/D2150	65
LT185/75R16	100/97R 8PR	BSW	26.9	7.3	5.0	5.0	6.0	12/32	S1764/D1609	65
LT215/70R15	104/101Q 8PR	BSW	26.9	8.5	5.5	6.0	6.5	14/32	S1984/D1819	65
LT215/85R16*	115/112Q 10PR	BSW	30.4	8.8	5.5	6.0	7.0	14/32	S2680/D2470	80
LT225/70R15	106/103Q 8PR	BSW	27.4	8.9	6.0	6.5	7.0	15/32	S2094/D1929	65
LT225/75R16*	115/112Q 10PR	BSW	29.3	9.1	6.0	6.0	7.0	12/32	S2680/D2470	80
LT235/85R16*	120/116Q 10PR	BSW	31.7	9.6	6.0	6.5	7.5	15/32	S3042/D2778	80
LT245/75R16*	120/116Q 10PR	BSW	30.5	10.0	6.5	7.0	8.0	14/32	S3042/D2778	80
LT265/75R16*	123/120Q 10PR	BSW	31.7	10.8	7.0	7.5	8.0	14/32	S3415/D3085	80
LT235/80R17*	120/117Q 10PR	BSW	31.7	9.3	6.0	6.5	7.5	14/32	S3085/D2835	80
LT245/70R17	119/116Q 10PR	BSW	30.6	9.5	6.5	7.0	8.0	14/32	S3000/D2778	80
145R12C	81/79P 6PR	BSW	21.3	5.8	3.5	4.0	4.5	9/32	S1170/D1100	65
145R12C	86/84N 8PR	BSW	21.3	5.7	3.5	4.0	4.5	9/32	S1168/D1102	65
155R12C	88/86N 8PR	BSW	21.9	6.0	4.0	4.5	5.0	11/32	S1235/D1168	65
155R13C	90/88N 8PR	BSW	22.9	6.1	4.0	4.5	5.0	11/32	S1323/D1235	65
155R13C	91/89N 8PR	BSW	22.9	6.2	4.0	4.5	5.0	11/32	S1356/D1280	65
165R13C	94/93R 8PR	BSW	23.5	6.6	4.0	4.5	5.0	11/32	S1477/D1433	65
175R13C	97/95N 8PR	BSW	24.1	6.9	4.5	5.0	5.5	11/32	S1609/D1521	65
165R14C	97/95N 8PR	BSW	24.6	6.7	4.0	4.5	5.0	11/32	S1609/D1521	65
175R14C	99/98N 8PR	BSW	25.1	6.9	4.5	5.0	5.5	11/32	S1709/D1655	65
185R14C	102/100R 8PR	BSW	25.7	7.2	5.0	5.0	6.0	12/32	S1874/D1765	65
195R14C	106/104R 8PR	BSW	26.3	7.7	5.0	5.5	6.0	12/32	S2094/D1984	65
205R14C	109/107Q 8PR	BSW	27.1	8.3	5.5	6.0	6.5	12/32	S2270/D2150	65
185R15C	103/102Q 8PR	BSW	26.6	7.3	5.0	5.0	6.0	12/32	S1929/D1874	65



*3-ply sidewall; BSW - Black Sidewall

BRAVO | UE-168(N) CONTINUED



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
195R15C	106/104R 8PR	BSW	27.3	7.8	5.0	5.5	6.0	12/32	S2095/D1985	65
155/70R12C	104/102N 6PR	BSW	20.7	6.1	4.5	4.5	5.0	11/32	S1984/D1874	94
165/70R13C	88/86S 6PR	BSW	22.1	6.5	4.5	5.0	5.0	12/32	S1235/D1168	54
175/70R14C	95/93S 6PR	BSW	23.7	6.9	4.5	5.0	5.5	12/32	S1521/D1433	54
205/70R14C	102/100Q 8PR	BSW	25.4	8.3	5.5	6.0	6.5	14/32	S1874/D1764	54
215/75R14C	112/110Q 8PR	BSW	26.7	8.5	5.5	6.0	7.0	13/32	S2469/D2337	69
205/70R15C	106/104R 8PR	BSW	26.3	8.1	5.0	6.0	7.0	14/32	S2094/D1984	65
215/70R15C	109/107R 8PR	BSW	26.9	8.5	5.5	6.5	7.0	14/32	S2270/D2149	65
225/70R15C	112/110R 8PR	BSW	27.4	9.1	6.0	6.5	7.0	14/32	TBD	TBD
225/70R15C*	116/114Q 10PR	BSW	27.4	9.1	6.0	6.5	7.0	14/32	S2778/D2600	69
175/75R16C	101/99R 8PR	BSW	26.3	7.1	4.5	5.0	5.5	12/32	S1819/D1708	69
185/75R16C	104/102R 8PR	BSW	26.9	7.4	5.0	5.5	6.0	12/32	S1984/D1875	69
195/75R16C	107/105R 8PR	BSW	27.5	7.9	5.0	5.5	6.0	12/32	S2149/D2039	69
195/75R16C*	110/108N 10PR	BSW	27.5	7.9	5.0	5.5	6.0	12/32	S2335/D2205	76
205/75R16C	110/108R 8PR	BSW	28.1	8.1	5.5	6.0	6.5	12/32	S2337/D2205	69
205/75R16C	113/111R 10PR	BSW	28.1	8.2	5.5	6.0	6.5	12/32	S2535/D2405	76
215/65R16C	109/107Q 8PR	BSW	27.1	8.5	6.0	6.5	7.5	14/32	S2271/D2149	69
215/70 R16C	108/106R 8PR	BSW	28.0	8.5	5.5	6.5	7.0	14/32	S2205/D2094	70
215/70R16C	116/114Q 10PR	BSW	28.0	8.5	5.5	6.5	7.0	14/32	S2755/D2600	76
215/75R16C	113/111R 8PR	BSW	28.7	8.8	5.5	6.0	7.0	12/32	S2535/D2381	69
215/75R16C	113/111S 8PR	BSW	28.7	8.7	5.5	6.0	7.0	12/32	S2535/D2381	69
225/75R16C	116/114Q 8PR	BSW	29.3	9.1	6.0	6.0	7.0	12/32	S2778/D2600	69
225/75R16C*	121/120R 10PR	BSW	29.3	8.9	6.0	6.0	7.0	12/32	S3195/D3085	83

VANSMART | MCV3+



TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
175R14C	99/98Q 8PR	BSW	25.0	6.9	4.5	5.0	5.5	13/32	S1709/D1653	65
185R14C	102/100R 8PR	BSW	25.6	7.3	5.0	5.0	6.0	13/32	S1874/D1764	65
195R14C	106/104R 8PR	BSW	26.2	7.7	5.0	5.5	6.0	13/32	S2094/D1984	65
205R14C	109/107Q 8PR	BSW	27.0	8.1	5.5	6.0	6.5	13/32	S2271/D2149	65
185R15C	103/102R 8PR	BSW	26.5	7.3	5.0	5.0	6.0	13/32	S1929/D1874	65
195/70R15C	104/102S 8PR	BSW	25.8	7.7	5.5	6.0	6.0	13/32	S1984/D1874	65
205/65R15C	102/100T 6PR	BSW	25.5	8.1	5.5	6.0	6.5	13/32	S1874/D1764	54
205/70R15C	106/104R 8PR	BSW	26.3	8.1	5.5	6.0	6.5	13/32	S2094/D1984	65
215/65R15C	104/102T 6PR	BSW	26.0	8.5	6.0	6.5	7.0	13/32	S1984/D1874	54
215/70R15C	109/107S 8PR	BSW	26.9	8.5	5.5	6.5	7.0	13/32	S2271/D2149	65

*3-ply sidewall; BSW - Black Sidewall; TBD - To Be Determined

VANSMART | MCV3+ CONTINUED

TIRE SIZE	SERVICE DESCRIPTION	SIDEWALL	OVERALL DIAMETER (IN.)	SECTION WIDTH (IN.)	MINIMUM RIM WIDTH (IN.)	NOMINAL RIM WIDTH (IN.)	MAXIMUM RIM WIDTH (IN.)	TREAD DEPTH (IN.)	MAX LOAD (LBS)	MAX INFL. PRESSURE (PSI)
225/70R15C	112/110S 8PR	BSW	27.4	8.9	6.0	6.5	7.0	14/32	S2469/D2337	65
175/75R16C	101/99R 8PR	BSW	26.3	6.9	4.5	5.0	5.5	13/32	S1819/D1709	69
185/75R16C	104/102R 8PR	BSW	26.9	7.3	5.0	5.0	6.0	13/32	S1984/D1874	69
195/60R16C	99/97T 6PR	BSW	25.2	7.7	5.5	6.0	6.5	13/32	S1709/D1609	54
195/65R16C	104/102T 8PR	BSW	26.0	7.7	5.5	6.0	6.0	13/32	S1984/D1874	69
195/75R16C	107/105S 8PR	BSW	27.5	7.7	5.0	5.5	6.0	13/32	S2149/D2039	69
205/65R16C	107/105T 8PR	BSW	26.5	8.1	5.5	6.0	6.5	13/32	S2149/D2039	69
205/75R16C	110/108R 8PR	BSW	28.1	8.1	5.5	5.5	6.5	13/32	S2337/D2205	69
205/75R16C	113/111R 10PR	BSW	28.1	8.1	5.5	5.5	6.5	13/32	S2535/D2403	76
215/60R16C	103/101T 6PR	BSW	26.1	8.5	6.0	6.5	7.0	13/32	S1929/D1819	54
215/65R16C	109/107T 8PR	BSW	27.0	8.5	6.0	6.5	7.0	13/32	S2271/D2149	69
215/70R16C	108/106T 8PR	BSW	27.9	8.5	5.5	6.5	7.0	13/32	S2205/D2094	54
215/75R16C	113/111R 8PR	BSW	28.7	8.5	5.5	6.0	7.0	13/32	S2535/D2403	69
225/65R16C	112/110T 8PR	BSW	27.5	8.9	6.0	6.5	7.0	13/32	S2469/D2337	69
225/75R16C	121/120R 10PR	BSW	29.3	8.9	6.0	6.0	7.0	13/32	S3197/D3086	83
235/65R16C	115/113T 8PR	BSW	28.0	9.3	6.5	7.0	7.5	13/32	S2679/D2535	69
285/65R16C	128N 10PR	BSW	30.6	11.2	8.0	8.5	9.0	13/32	TBD	76
215/60R17C	109/107T 8PR	BSW	27.2	8.5	6.0	6.5	7.0	13/32	S2271/D2149	69
225/55R17C	109/107H 8PR	BSW	26.8	8.9	6.5	7.0	7.5	13/32	S2271/D2149	69





MAXXIS[®]
TIRES